



	<a href="#">AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-HFW1801TLM-IL-A-0360B-S2 - 8.3 Mpx 3.6 mm DAHUA</a>	<a href="#">AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-HFW1500TL-A-0360B-S2 - 5 Mpx 3.6 mm DAHUA</a>
		
	1027.74 DKK 1027.74 DKK	627.67 DKK 627.67 DKK
Standard	AHD, HD-CVI, HD-TVI, CVBS	AHD, HD-CVI, HD-TVI, CVBS
Sensor	Progressive Scan CMOS	1/2.7 " Progressive Scan CMOS
Matrix size	8.3 Mpx	5 Mpx
Resolution	3840 x 2160 - 8.3 Mpx @ HD-CVI @ 25 fps , 3840 x 2160 - 8.3 Mpx @ HD-CVI / HD-TVI / AHD @ 15 fps , 2592 x 1944 - 5 Mpx @ HD-CVI @ 25 fps , 2560 x 1440 - 3.7 Mpx @ HD-CVI @ 25 fps , 1920 x 1080 - 1080p @ HD-CVI @ 25 fps , 960 x 576 - 960H @ PAL @ 25 fps	2880 x 1620 - 5 Mpx HD-CVI only , 2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p HD-CVI only 960 x 576 - 960H
Lens	3.6 mm	3.6 mm
View angle	<ul style="list-style-type: none"> <li>• 88 ° (manufacturer data)</li> <li>• 82 ° (our tests result)</li> </ul>	<ul style="list-style-type: none"> <li>• 92 ° (manufacturer data)</li> <li>• 90 ° (our tests result)</li> </ul>
Range of IR illumination	40 m	80 m
White light LED illuminator range	40 m	...
IR illuminator power adjustment	Automatic	Automatic
Video output	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω
Audio	<ul style="list-style-type: none"> <li>• Microphone built-in,</li> <li>• Audio support via coaxial cable - HD-CVI only</li> </ul>	Microphone built-in, HD-CVI only
OSD menu	✓	✓

Main features	<ul style="list-style-type: none"> <li>• Smart Dual Illumination technology - IR or LED illuminator works in night mode. White light will turn on automatically only when an object is detected in the monitored area, which effectively improves image quality</li> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• F-DNR (Defog) - Reduction of image noise caused by precipitation</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• ICR - Movable InfraRed filter</li> <li>• AGC - Automatic Gain Control</li> <li>• Privacy zones - max. 8</li> <li>• Mirror - Mirror image</li> <li>• Auto White Balance</li> <li>• Sharpness - sharper image outlines</li> </ul>	<ul style="list-style-type: none"> <li>• D-WDR - Wide Dynamic Range</li> <li>• 2D-DNR - Digital Noise Reduction</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• Day/night mode</li> <li>• ICR - Movable InfraRed filter</li> <li>• Auto White Balance</li> <li>• AGC - Automatic Gain Control</li> <li>• Sharpness - sharper image outlines</li> <li>• Privacy zones</li> <li>• Mirror - Mirror image</li> </ul>
Power supply	12 V DC / 480 mA	12 V DC / 430 mA
Power consumption	≤ 5.7 W	≤ 5.2 W
Housing	Compact Plastic + Metal	Compact, Plastic + Metal
Color	White	White + Black
"Index of Protection"	IP67	IP67
Vandal-proof	—	...
Operation temp	-40 °C ... 60 °C	-40 °C ... 60 °C
Weight	0.3 kg	0.28 kg
Dimensions	198 x 80 x 76 mm	199 x 80 x 76 mm
Manufacturer / Brand	DAHUA	DAHUA
Guarantee	3 years	3 years