





	SWITCH POE GTX-B1-10-82G 8-PORT	TV OR MONITOR MOUNT AX-FLEXI-APOLLO	TV OR MONITOR CEILING MOUNT BRATECK-LCD-CM344	TV OR MONITOR MOUNT AX-FLEXI-42
				
	532.18 DKK 532.18 DKK	125.94 DKK 125.94 DKK	126.70 DKK 126.70 DKK	49.55 DKK 49.55 DKK
LAN ports	<ul style="list-style-type: none"> • 8 x RJ45 (1 x Hi-PoE + 7 x PoE (802.3af/at)), • 2 x RJ45 - Uplink
Mounting standard	...	VESA 50, 75, 100, 200 x 100, 200	VESA 75, 100, 100 x 200, 200, 200 x 300, 300, 200 x 400, 400	VESA 75, 100, 200 x 100, 200
Screen size range	...	17 " ... 42 "	23 " ... 55 "	13 " ... 42 "
Distance from mounting surface	...	89 ... 466 mm	...	56 ... 230 mm from wall
Bearing capacity	...	35 kg	20 kg	25 kg
Color	...	Black	Black	Black
Tilt adjustment	...	-15 ° ... 15 °	-90 ° ... 0 °	-5 ° ... 15 °
Management	—
Horizontal rotation	...	Articulated arm with two swivels in range -90 ° ... 90 ° each	-45 ° ... 45 °	Articulated arm with two swivels in range -90 ° ... 90 ° each
Rotation in the plane of the screen	...	—	—	—
LED diodes	Power, V - VLAN (Port Isolation), S - Extend, PoE, Link/Act, Speed
Manufacturer / Brand	BRATECK	...
Transmission speed	<ul style="list-style-type: none"> • 10 / 100 / 1000 Mbps : 2 x Port LAN - Uplink, • 10 / 100 Mbps : 8 x Port LAN & PoE
Operation modes	<ul style="list-style-type: none"> • N - Normal - the device operates as normal PoE switch • V - VLAN (Port Isolation) - 1 ... 8 ports are isolated from each other and separately work with the 9, 10 ports • S - Extend - Range : 250 m @ 10 Mbps
Maximal output power	<ul style="list-style-type: none"> • 60 W / port Hi-PoE - Port 1 • 30 W / port PoE - 2 ... 8 ports
Maximal total power	120 W
MAC addresses table	2k



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Main features	<ul style="list-style-type: none"> • MDI/MDI-X auto detection feature - auto detecting the data transmission mode • Full Duplex: IEEE802.3x, Half Duplex: Back Pressure • Auto-learning and Auto-aging functions support for MAC addresses • PD Alive mode - monitoring of the ports that power PoE devices and automatic restart by cutting off the power supply when an unresponsive device is detected • MTBF (Mean Time Between Faults) : 50000 h 	...	<ul style="list-style-type: none"> • Adjustable distance from the ceiling • Foldable design - screen and arm out of the way when not in use - space saving 	...
Certificates	CE, FCC Class B
Protections	Overvoltage \pm 4 kV
Power supply	100 ... 265 V AC
Operation temp	-10 °C ... 45 °C
Weight	0.77 kg	1.83 kg	1.8 kg	1.15 kg
Dimensions	210 x 150 x 35 mm	220 x 300 x (89 ... 466) mm	520 ... 614 x 435 x 165 mm	220 x 220 x (56 ... 230) mm
Guarantee	2 years	2 years	2 years	2 years

