



	POLE MOUNT BCS-V-AS BCS View	POWER DISTRIBUTION UNIT ACAR-XPROTECTOR
		
	55.07 EUR 55.07 EUR	20.38 EUR 20.38 EUR
Suitable for cameras	BCS View	...
Rated voltage	...	230 V AC / 50 Hz
Total maximal current	...	10 A
Pole diameters range	Ø 67 ... Ø 127 mm	...
Maximal total load	...	2300 W
Material	Stainless steel	...
Response time	...	< 25 ns
Color	White	...
Number of outlets	...	5 grounded outlets 10A/250V
Manufacturer / Brand	BCS View	...
Automatic delayed fuse	...	10 A / 250 V
Leak current	...	< 0.5 mA
Nominal voltage of surge suppressor	...	250 V / 50 Hz
Protection level of surge suppressor	...	≤ 1.3 kV (L/N)
Nominal stroke current	...	1 kA (L/N) - (8/20µs)
Switch	...	two-way, with light indication
Maximum stroke current	...	4.5 kA (L/N) - (8/20µs)
Length of the cable	...	1.45 m
Housing	...	Plastic - non-flammable
Dimensions	127 x 250 x 46 mm	365 x 65 x 52 mm
Weight	1.5 kg	0.51 kg
Guarantee	3 years	2 years