



	PATCHCORD UC-PATCH-2M-RJ45-BK 2.0 m UBIQUITI	NVR NVR616DH-128-XI 128 CHANNELS WizMind DAHUA
		
	4.92 EUR 4.92 EUR	10142.29 EUR 10142.29 EUR
Standard	...	IP
Supported resolutions	...	max. 32 Mpx
Cable	UTP cat. 6 : RJ-45 - Plug / RJ-45 - Plug	...
Color	Black	...
Length of the cable	2.0 m	...
Video outputs	...	<ul style="list-style-type: none"> • 2 pcs HDMI 4K • 1 pcs HDMI 8K • 1 pcs HDMI • 2 pcs VGA
Main features	<ul style="list-style-type: none"> • Very flexible • Ultra-thin 3 mm thick patchcord • Very easy and quick assembly • Corrosion resistance 	...
Audio support	...	<ul style="list-style-type: none"> • 128 Channels - Audio from cameras, • Bi-directional audio streaming support • Audio detection
Audio inputs	...	1 pcs CINCH
Audio outputs	...	2 pcs CINCH
Image compression method	...	Smart H.265+ / H.265 / Smart H.264+ / H.264
Bitrate	...	max. 1280 Mbps
Supported hard drives	...	16 x 20 TB SATA + 1 x eSATA , Raid 0/1/5/6/10
Recording modes	...	Manual, Sensor, Motion detection, Schedule
External storage devices backup	...	Backup to USB drive (pendrive, external drive)
Searching and playback the records	...	<ul style="list-style-type: none"> • Records searching: by time and events type. Records playback: forward, backward, fast, slow • Advanced searching (to the one second accuracy) • Smart Playback function • Records playback from max. 16 channels in the same time
Network interface	...	4 x RJ-45 10/100/1000/2500 Base-TX
Network functions	...	Full support via network, Remote records copying, Web-Server built-in
ONVIF	...	22.06
Default IP address	...	192.168.1.108
Default admin user / password	...	admin / - The administrator password should be set at the first start

Mobile phones support	...	<p>Port no.: 37777 or access by a cloud (P2P)</p> <ul style="list-style-type: none"> • Android: Free application DMSS • iOS (iPhone): Free application DMSS <p>See how to configure the P2P function in Dahua recorders and how to enable the mobile application</p>
Web browser access ports	...	80, 37777
PC client access ports	...	37777
Mobile client access ports	...	37777
RTSP URL	...	<ul style="list-style-type: none"> • rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream • rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream
USB	...	<ul style="list-style-type: none"> • 2 pcs USB 2.0 • 2 pcs USB 3.0
Serial ports	...	<ul style="list-style-type: none"> • 2 pcs RS-485 • 1 pcs RS-232
Alarm inputs / outputs	...	32 / 16
PTZ control	...	<ul style="list-style-type: none"> • IP Speed Dome Cameras • RS-485 - PELCO-D/P and others
Intelligent image analysis	...	✓
Motion Detection	...	✓
Main features	...	<ul style="list-style-type: none"> • Panel with LCD display, • Intelligent image analysis : IVS analysis - 10 rules, scene changing, face detection, • SMD PLUS - searching for an object classified as: human, motor vehicle, non-motor vehicle • Filtering of false alarms based on the recognition of persons and vehicles • Face recognition - supports 6 types of facial attributes extraction • Face recognition and analysis in real time (up to 16 photos per second) • Support for up to 40 face databases, including 300 000 face images • metadata handling - automatic photo taking and collection of information enabling the subsequent identification of people and vehicles that triggered the alarm (clothing, silhouette, face, features of motor and non-mechanical vehicles) • AcuPick support - technology that uses artificial intelligence on both front-end and back-end to search through massive amounts of video data to quickly locate targets with high precision • EPTZ - advanced target detection and tracking algorithms that trigger alarms - can simultaneously zoom and track many people and/or vehicles <p>Functions implemented in cooperation between the recorder and cameras that support these functions :</p> <ul style="list-style-type: none"> • ANPR • Authorized and unauthorized license plate lists: up to 20 000 records • counting people / vehicles • crowd gathering estimation • heat map



Mouse support	...	✓
IR remote controller in the set	...	—
Switch PoE	...	—
Power supply	...	100 ... 240 V AC @ 50 ± 2 Hz
Power consumption	...	max. 25 W (without HDD)
Operation temp	...	-10 °C ... 55 °C
Weight	0.03 kg	12.83 kg
Dimensions	...	485 x 522 x 133 mm
Supported languages	...	Polish, English
Manufacturer / Brand	UBIQUITI	DAHUA
Guarantee	2 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00