

	MOUNT RACK FRAME A19S-1U	UNIVERSAL METER RB-10B REBEL Tools	POWER DISTRIBUTION UNIT WITH REMOTE CONTROL OR-AE-13132 (5 OUTLETS) ORNO
			
	4367.62 HUF 4367.62 HUF	5691.43 HUF 5691.43 HUF	16694.29 HUF 16694.29 HUF
Rated voltage	230 V AC / 50 Hz
Total maximal current	10 A
Maximal total load	2300 W
Number of outlets	5 grounded outlets 10A/250V
Socket type	CEE 7/5 E type
Plug type	CEE 7/7
Switch	—
Length of the cable	3 m
Wireless	<ul style="list-style-type: none"> • 433.92 MHz • Remote control • Operating range in open area : 30 m
DC voltage measurement	...	400 mV ± (0.8% + 5) @ 0.1 mV , 4 V ± (0.8% + 3) @ 0.001 V , 40 V ± (0.8% + 3) @ 0.01 V ... , 400 V ± (0.8% + 3) @ 0.1 V , 600 V ± (1.0% + 5) @ 1 V	
Housing	Plastic
Color	Black	...	Black
AC voltage measurement	...	400 mV ± (1.2% + 8) @ 1 mV , 4 V ± (1.0% + 8) @ 0.001 V , 40 V ± (1.0% + 8) @ 0.01 V ... , 400 V ± (1.0% + 8) @ 0.1 V , 600 V ± (1.2% + 8) @ 1 V	
DC current measurement	...	—	...
AC current measurement	...	—	...

Resistance measurement	...	400 Ω ± (1.2% + 8) @ 0.1 Ω , 4 kΩ ± (1.2% + 5) @ 0.001 kΩ , 40 kΩ ± (1.2% + 5) @ 0.01 kΩ , 400 kΩ ± (1.2% + 5) @ 0.1 kΩ , 4 MΩ ± (1.2% + 5) @ 0.001 MΩ , 40 MΩ ± (1.5% + 5) @ 0.01 MΩ	...
Capacitance measurement	...	40 nF ± (5% + 10) @ 0.01 nF , 400 nF ± (5% + 5) @ 0.1 nF , 4 μF ± (5% + 5) @ 0.001 μF , 40 μF ± (5% + 5) @ 0.01 μF , 100 μF ± (5% + 5) @ 0.1 μF	...
Inductance measurement	...	—	...
Frequency measurement	...	5 Hz ± (1% + 3) @ 0.001 Hz , 50 Hz ± (1% + 3) @ 0.01 Hz , 500 Hz ± (1% + 3) @ 0.1 Hz , 5 kHz ± (1% + 3) @ 0.001 kHz , 50 kHz ± (1% + 3) @ 0.01 kHz , 500 kHz ± (1% + 3) @ 0.1 kHz , 5 MHz ± (1% + 3) @ 0.001 MHz	...
Square-wave signal duty ratio measurement	...	0.1 ... 99.9 % @ 0.1 %	...
Temperature measurement	...	—	...
Automatic change of measuring ranges	...	✓	...
hFE	...	—	...
Diode test	...	✓	...
Sound signal of the continuity test	...	✓	...
Checking TTL logic states	...	—	...
RS-232	...	—	...

Main features	...	<ul style="list-style-type: none"> • Large, readable LCD display • Freezing the last reading • Low battery level alarm • Aesthetic and solid construction • The set includes a practical case 	<ul style="list-style-type: none"> • radio remote controller in the set • Remote controlled : Supports max. 5 devices • LED indicators displaying the device's operating status • Overload protection • Current paths shutters • Insulation - PVC • Wire gauge : 3 x 1.5 mm² • "Index of Protection" : IP20
Power supply	...	1 x CR2032 lithium battery - included	<ul style="list-style-type: none"> • 230 V AC, 50 Hz • Remote control : 12V, type A23 battery (included)
Weight	0.53 kg	0.1 kg	0.92 kg
Dimensions	490 x 102 x 55 mm - RACK 19", 1U	117 x 77 x 18 mm	390 x 68 x 45 mm
Manufacturer / Brand	...	REBEL Tools	ORNO
Guarantee	2 years	2 years	2 years