

	<a href="#">ISOPROPYL ALCOHOL KONTAKT-IPA-PLUS/5000 METAL CANISTER 5 l AG TERMOPASTY</a>	<a href="#">IP CAMERA DS-2CD2T46G2P-ISU/SL(2.8MM)(C) PANORAMIC ACUSENSE - 4.1 Mpx 2 x 2.8 mm Hikvision</a>
		
	29.21 EUR 29.21 EUR	422.90 EUR 422.90 EUR
Standard	...	TCP/IP
Package	Metal canister 5 l	...
Application	Ideal for removing dirt from optical components	...
Sensor	...	2 x 1/2.5 " Progressive Scan CMOS
Matrix size	...	2 x 2 Mpx - 4.1 Mpx (total)
Resolution	...	3140 x 1368 - 4.1 Mpx
Lens	...	2 x 2.8 mm
View angle	...	180 ° (horizontal) 44 ° (vertical)
Range of IR illumination	...	40 m
RS-485 interface	...	—
Image compression method	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Alarm inputs / outputs	...	1 / 1
Audio	...	<ul style="list-style-type: none"> <li>• Microphone built-in,</li> <li>• External microphone input</li> <li>• Audio output</li> <li>• Bi-directional audio streaming support</li> <li>• Digital Noise Reduction</li> </ul>
Main stream frame rate	...	25 fps @ 4.1 Mpx
Network interface	...	10/100 Base-T (RJ-45)
Memory card slot	...	Micro SD memory cards up to 512GB support (possible local recording)
Mobile phones support	...	Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none"> <li>• Android: Free application <a href="#">Hik-Connect</a></li> <li>• iOS: Free application <a href="#">Hik-Connect</a></li> </ul>
Default admin user / password	...	admin / - The administrator password should be set at the first start
Default IP address	...	192.168.1.64
Web browser access ports	...	80
PC client access ports	...	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application

Mobile client access ports	...	8000
Port ONVIF	...	80
RTSP URL	...	<ul style="list-style-type: none"> <li>• Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ - with authorization</li> <li>• Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/ - with authorization</li> </ul>
WEB Server	...	Built-in
Max. number of on-line users	...	6
ONVIF	...	✓
Main features	...	<ul style="list-style-type: none"> <li>• Camera from AcuSense series</li> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• NAS - Network Attached Storage support</li> <li>• ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its</li> <li>• SVC (Scalable Video Coding) - technology enabling the transfer of several sub-streams of different quality within one stream</li> <li>• Active deterrence function - Light and sound alarm</li> <li>• White light (LED) illuminator built-in : 4 LEDs</li> <li>• BLC - Back Light Compensation</li> <li>• HLC - High Light Compensation (spot)</li> <li>• AGC - Automatic Gain Control</li> <li>• Possibility to change the resolution, quality and bit rate</li> <li>• Configurable: brightness, contrast, saturation</li> <li>• Smart motion detection (with recognizing people and vehicles)</li> <li>• Intelligent image analysis - crossing the line (tripwire), intrusion, detection of entry into the area / exit from the area - classification of people and vehicles, scene changing</li> </ul>
Power supply	...	<ul style="list-style-type: none"> <li>• 12 V DC / 880 mA,</li> <li>• PoE (802.3af)</li> </ul>
Power consumption	...	<ul style="list-style-type: none"> <li>• ≤ 10.5 W @ 12 V DC</li> <li>• ≤ 12.5 W @ PoE</li> </ul>
Housing	...	Compact, Metal
Color	...	White
Vandal-proof	...	—
"Index of Protection"	...	IP67
Operation temp	...	-30 °C ... 60 °C
Weight	4.371 kg	1.43 kg
Dimensions	315 x 168 x 105 mm	119 x 105 x 307 mm
Supported languages	...	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Ukrainian, Hungarian, Italian
SAP Code	...	311320496

Manufacturer / Brand	AG TERMOPASTY	Hikvision
Guarantee	...	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00