



	<a href="#">IP VANDALPROOF CAMERA IPC-HDBW5431E-ZE-27135 - 4.0 Mpx, 2.7 ... 13.5 mm - MOTOZOOM DAHUA</a>	<a href="#">SWITCH POE GTX- CLM1-10-8G2G 8-PORT</a>
		
	543.26 CAD 543.26 CAD	212.07 CAD 212.07 CAD
Standard	TCP/IP	...
Sensor	1/3 " Progressive Scan CMOS	...
Matrix size	4.0 Mpx	...
LAN ports	...	<ul style="list-style-type: none"> <li>• 8 x RJ45 ( 2 x Hi-PoE + 6 x PoE (802.3af/at) ),</li> <li>• 2 x RJ45 - Uplink</li> </ul>
Management	...	✓
Transmission speed	...	10 / 100 / 1000 Mbps : 2 x Port LAN - Uplink + 8 x Port LAN & PoE
Resolution	2688 x 1520 - 4.0 Mpx , 2560 x 1440 - 3.6 Mpx , 2304 x 1296 - 3.0 Mpx , 1920 x 1080 - 1080p 1280 x 1024 - 1.4 Mpx 1280 x 960 - 1.3 Mpx 1280 x 720 - 720p	...
Operation modes	...	<ul style="list-style-type: none"> <li>• N - Normal - the device operates as normal PoE switch</li> <li>• V - VLAN (Port Isolation) - 1 ... 8 ports are isolated from each other and separately work with the 9, 10 ports</li> <li>• S - Extend - Range : 250 m @ 10 Mbps</li> </ul>
Maximal output power	...	<ul style="list-style-type: none"> <li>• 90 W / port Hi-PoE - 1, 2 ports</li> <li>• 30 W / port PoE - 3 ... 8 ports</li> </ul>
Maximal total power	...	120 W
Main features	...	<ul style="list-style-type: none"> <li>• MDI/MDI-X auto detection feature - auto detecting the data transmission mode</li> <li>• Auto-learning and Auto-aging functions support for MAC addresses</li> <li>• QoS - mechanisms, which provide the high quality of transmission</li> <li>• MTBF (Mean Time Between Faults) : 50000 h</li> </ul>
LED diodes	...	PWR, PoE, Link/Act
Certificates	...	CE, FCC, RoHS
Protections	...	Overvoltage ± 4 kV

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Lens	2.7 ... 13.5 mm - Motozoom	...
Operation temp	...	-10 °C ... 55 °C
View angle	<ul style="list-style-type: none"> <li>• 106 ° ... 31 ° (manufacturer data)</li> <li>• 102 ° ... 28 ° (our tests result)</li> </ul>	...
Range of IR illumination	50 m	...
S/N ratio	> 50 dB	...
RS-485 interface	—	...
Memory card slot	Micro SD memory cards up to 128GB support (possible local recording)	...
Image compression method	H.265 / H.265+ / H.264 / H.264+ / MJPEG	...
Alarm inputs / outputs	1 / 1	...
Audio	<ul style="list-style-type: none"> <li>• External microphone input</li> <li>• Audio output</li> <li>• Bi-directional audio streaming support</li> <li>• Audio detection</li> </ul>	...
Bitrate	24 kb/s ... 10240 kb/s @ H.264	...
Network interface	10/100 Base-T (RJ-45)	...
Network protocols	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour	...
WEB Server	Built-in, Web Viewer	...
Max. number of on-line users	20	...
ONVIF	16.12	...
Main stream frame rate	25 fps @ 4.0 Mpx	...
Mobile phones support	Port no.: 37777 or access by a cloud (P2P) <ul style="list-style-type: none"> <li>• Android: Free application <a href="#">DMSS</a></li> <li>• iOS (iPhone): Free application <a href="#">DMSS</a></li> </ul>	...
Default IP address	192.168.1.108	192.168.2.1
Default admin user / password	admin / admin	admin / admin
Web browser access ports	80, 37777	...
PC client access ports	37777	...
Mobile client access ports	37777	...
Port ONVIF	80	...
RTSP URL	rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream	...



Main features	<ul style="list-style-type: none"> <li>• Motozoom lens</li> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• ICR - Movable InfraRed filter</li> <li>• Motion Detection</li> <li>• IVS analysis : crossing the line (tripwire), intrusion, abandoned/missing object, face detection</li> <li>• WB - White Balance (ATW/AWB/manual/indoor/outdoor)</li> <li>• BLC - configurable Back Light Compensation</li> <li>• HLC - High Light Compensation (spot)</li> <li>• Configurable Privacy Zones</li> <li>• D-ZOOM - Digital Zoom</li> <li>• Mirror - Mirror image</li> <li>• Sharpness - sharper image outlines</li> </ul>	...
Power supply	<ul style="list-style-type: none"> <li>• PoE (802.3at),</li> <li>• ePoE,</li> <li>• 12 V DC / 1250 mA,</li> <li>• 24 V AC / 620 mA</li> </ul>	48 ... 57 V DC, Power adapter included
Power consumption	≤ 15 W	...
Housing	Dome - Metal	Metal
Color	White	...
"Index of Protection"	IP67	...
Vandal-proof	IK10	...
Operation temp	-30 °C ... 60 °C	...
Weight	0.88 kg	0.45 kg
Dimensions	Ø 159 x 118 mm	185 x 95 x 27 mm
Supported languages	English, Polish	...
Manufacturer / Brand	DAHUA	...
Guarantee	3 years	2 years

