




	SWITCH POE GTX-A1-06-42 4-PORT	SWITCH POE GTX-A1-10-82 8-PORT	WIRELESS REMOTE CONTROL WITH KEYBOARD KS-3 Air Mouse 2.4 GHz Blow
			
	35.64 CHF 35.64 CHF	63.40 CHF 63.40 CHF	10.68 CHF 10.68 CHF
Operating frequency	2.4 GHz
Operation range	~ 10 m
LAN ports	<ul style="list-style-type: none"> • 4 x RJ45 (1 x Hi-PoE + 3 x PoE (802.3af/at)), • 2 x RJ45 - Uplink 	<ul style="list-style-type: none"> • 8 x RJ45 (1 x Hi-PoE + 7 x PoE (802.3af/at)), • 2 x RJ45 - Uplink 	...
Housing	Plastic
Color	Black
Management	—	—	...
Current consumption	<ul style="list-style-type: none"> • 8 ... 16 mA (operation) • 6 mA (Standby mode)
LED diodes	Power, V - VLAN (Port Isolation), S - Extend, PoE, Link/Act	Power, V - VLAN (Port Isolation), S - Extend, PoE, Link/Act	...
Transmission speed	10 / 100 Mbps : 2 x Port LAN - Uplink + 4 x Port LAN & PoE	10 / 100 Mbps : 2 x Port LAN - Uplink + 8 x Port LAN & PoE	...
Manufacturer / Brand	Blow
Operation modes	<ul style="list-style-type: none"> • N - Normal - the device operates as normal PoE switch • V - VLAN (Port Isolation) - 1 ... 4 ports are isolated from each other and separately work with the 5, 6 ports • S - Extend - Range : 250 m @ 10 Mbps 	<ul style="list-style-type: none"> • N - Normal - the device operates as normal PoE switch • V - VLAN (Port Isolation) - 1 ... 8 ports are isolated from each other and separately work with the 9, 10 ports • S - Extend - Range : 250 m @ 10 Mbps 	...
Maximal output power	<ul style="list-style-type: none"> • 60 W / port Hi-PoE - Port 1 • 30 W / port PoE - 2 ... 4 ports 	<ul style="list-style-type: none"> • 60 W / port Hi-PoE - Port 1 • 30 W / port PoE - 2 ... 8 ports 	...
Maximal total power	65 W	120 W	...
MAC addresses table	1k	1k	...

Main features	<ul style="list-style-type: none"> • MDI/MDI-X auto detection feature - auto detecting the data transmission mode • Full Duplex: IEEE802.3x, Half Duplex: Back Pressure • Auto-learning and Auto-aging functions support for MAC addresses • PD Alive mode - monitoring of the ports that power PoE devices and automatic restart by cutting off the power supply when an unresponsive device is detected • MTBF (Mean Time Between Faults) : 50000 h 	<ul style="list-style-type: none"> • MDI/MDI-X auto detection feature - auto detecting the data transmission mode • Full Duplex: IEEE802.3x, Half Duplex: Back Pressure • Auto-learning and Auto-aging functions support for MAC addresses • PD Alive mode - monitoring of the ports that power PoE devices and automatic restart by cutting off the power supply when an unresponsive device is detected • MTBF (Mean Time Between Faults) : 50000 h 	<ul style="list-style-type: none"> • Air Mouse function - The built-in gravity sensor allows you to control the mouse cursor on the device screen by holding the remote control and making movements in the air - this solution does not require any flat surface • Backlit full keyboard in QWERTY standard • Remote control - Basic operation of functions such as: volume control, menu operation, channel selection, turning on and off the connected device • The ergonomic shape • Illuminated buttons • Plug & Play • Compatible with Windows, Mac OS, Linux, Android systems • Cooperation with DAHUA, HIKVISION recorders • USB cable included
Certificates	CE, FCC Class B	CE, FCC Class B	...
Protections	Overvoltage \pm 3 kV	Overvoltage \pm 4 kV	...
Power supply	100 ... 265 V AC	100 ... 265 V AC	<ul style="list-style-type: none"> • built-in battery • Charging via micro USB port
Operation temp	-10 °C ... 55 °C	-10 °C ... 45 °C	...
Weight	0.6 kg	0.76 kg	0.053 kg
Dimensions	190 x 130 x 35 mm	210 x 150 x 35 mm	<ul style="list-style-type: none"> • 151 x 45 x 14 mm • 0.5 m (cable length)
Guarantee	2 years	2 years	2 years