

	SPEAKER MOUNT BRATECK-SB-24	ACCESS POINT 4G+ LTE +ROUTER RUT361 2.4 GHz 300 Mbps Teltonika	VIDEO BALUN TR-1/SV OPTO-ISOLATOR	ELECTRIC CABLE DY-2.5-BU/750V
				
	2.22 EUR 2.22 EUR	196.93 EUR 196.93 EUR	33.36 EUR 33.36 EUR	0.36 EUR 0.36 EUR
Frequency range	...	2.4 GHz
Standard	• CVBS - PAL, NTSC	...
In section	100 m . Price for 1m when buying a whole roll
In package	2 pcs The price for package
Video transmission range	max. 400 m UTP cat. 5e	...
Bearing capacity	3.5 kg
Distance from mounting surface	60 mm
Device type	Active	...
Inner conductor	2.5 mm ² - Cu wire
Tilt adjustment	± 20 °
Antenna type	...	2x2 MIMO : 2 x Omnidirectional antenna Wi-Fi - 5 dBi (SMA connector) , 2 x Omnidirectional antenna 4G LTE - 4 dBi (SMA-RP connector)
Coaxial socket voltage range 75Ω (CVBS)	1 Vpp	...
Rated voltage	450 / 750 V
Horizontal rotation	± 70 °
Outer coating	Ø 3.3 mm - PVC
Standards	...	IEEE 802.11 b/g/n, 4G+ Cat.6 LTE, 3G
Number of channels	1	...
Coating color	Blue
Video bandwidth	0 ... 9 MHz (-3 dB)	...
CMRR (dB @ 5MHz)	50 dB	...
Coaxial socket impedance	75 Ω	...
Symmetrical socket impedance	100 Ω	...
Baud rates	...	11n : 300 Mbps 11g : 54 Mbps 11b : 11 Mbps LTE : 300 / 42 Mbps (4G / 3G)
Opto-isolation between input and output	1000 V (peak)	...
Opto-isolation between power and signal inputs / outputs	1000 V (peak)	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

LAN ports	...	<ul style="list-style-type: none"> • 1 x 10/100 Mbps - WAN • 1 x 10/100 Mbps - LAN
Coaxial socket type	BNC Straight socket	...
Symmetrical socket type	Cable terminals	...
Transmitter power	...	≤ 17.51 dBm @ 2.4 GHz ≤ 23 dBm @ 4G LTE ≤ 24 dBm @ 3G WCDMA
LED indicators	...	Power, WAN, WLAN, LAN, LTE - 3G/4G, Signal indicator
Network type	...	4G, 3G
LTE	...	✓
QSS	...	—
WDS	...	—
DHCP server	...	✓
Protections	...	<ul style="list-style-type: none"> • WPA3-EAP • WPA3-SAE • WPA2-Enterprise - PEAP • WPA2-PSK • AES-CCMP • WEP • TKIP • Auto Cipher modes • Client separation • SSID hiding • MAC addresses filtering
Management interface	...	Web browser, Teltonika RMS application, SMS
Main features	...	<ul style="list-style-type: none"> • Support for IoT (Internet of Things) systems, • Ability to work as a Hotspot, • Support for VoIP technology, • Support for Mesh technology • SIM socket • DHCP Relay support • DHCP client list • Static / dynamic routing • VPN support • Default address : 192.168.1.1 • Configuration using the Teltonika RMS application • WAN Connection Backup - thanks to the fully functional WAN / LAN port, you can use various types of backup connections, including cable, fiber and DSL modems
Power supply	...	<ul style="list-style-type: none"> • 12 V DC / 1.5 A (power adapter included) • 9 ... 30 V DC 	12 V DC / 90 mA	...
Power consumption	...	≤ 4.7 W
Operation temp	...	-40 °C ... 75 °C	-50 °C ... 55 °C	...



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Permissible relative humidity	...	10 % ... 90 % (non-condensing)	< 95 %	...
Weight	0.06 kg	0.25 kg	0.095 kg	...
Dimensions	87 x 47 x 60 mm	100 x 93 x 30 mm	117 x 30 x 62 mm	...
Manufacturer / Brand	BRATECK	Teltonika	DELTA	...
Guarantee	2 years	2 years	3 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00