







	EXPANSION PLUG JPK-12X220/M5 EBOLT	SILICONE CAMERA COVER FRS10-B-IMOU	ISOPROPYL ALCOHOL CLEANSER-IPA/400 SPRAY 400 ml	CAMERA BRACKET BCS-V- UDAS BCS View	END CLAMP PV-KK/35-50/S FOR SOLAR PANELS 35 mm	HD-TVI VANDALPROOF CAMERA DS-2CE56D8T-VPIT3ZE(2.8-12MM) - 1080p PoC.at Hikvision
						
	1.99 EUR 1.99 EUR	8.40 EUR 8.40 EUR	6.47 EUR 6.47 EUR	111.59 EUR 111.59 EUR	0.43 EUR 0.43 EUR	168.11 EUR 168.11 EUR
Material	...	Silicon	Aluminum	...
Suitable for cameras	BCS View
Standard	HD-TVI
Height	35 mm	...
Package	Spray 400 ml
Sensor	Progressive Scan CMOS
Hole diameter	9 mm	...
Main features	Spray formulation with a straw for easy application in hard-to-reach places
Matrix size	2.1 Mpx
mounting screw	—	...
Material	• Expansion plug, Polypropylene • Screw, Steel galvanized • mounting screw, Steel galvanized	Aluminum alloy
Resolution	1920 x 1080 - 1080p @ HD-TVI
Drilling diameter	12 mm
Range of IR illumination	40 m
Expansion plug length	215 mm
IR illuminator power adjustment	Automatic
Screw dimensions	Ø 8 x 220 mm, Internal thread M5
Lens	2.8 ... 12 mm - Motozoom
Screw	Ø 5 x 16 mm
Application	for Styrofoam 150 mm
View angle	• 103 ° ... 32 ° (manufacturer data) • 92 ° ... 32 ° (our tests result)
Video output	1 Vpp / 75 Ω - HD-TVI, BNC socket
Main features	• Motozoom lens • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • Sense-UP - (Slow Shutter) - Increase the sensor sensitivity • EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners • The ability to power the camera via a coaxial cable according to the innovative PoC (Power over Coaxial) standard allows to eliminate the need for additional wiring to the unit • ICR - Movable InfraRed filter • Privacy zones - max. 4 • Motion Detection - max. 4 zones • Mirror - Mirror image • Sharpness - sharper image outlines
OSD menu	✓
Power supply	PoC.at , 12 V DC / 580 mA
Power consumption	≤ 7 W
Housing	Dome, Metal
Color	...	Black	...	White	Silver	White
"Index of Protection"	IP67
Vandal-proof	IK10
Operation temp	-40 °C ... 60 °C
Weight	...	0.03 kg	0.39 kg	2.85 kg	0.22 kg	0.93 kg
Dimensions	...	65 x 78 x 76 mm	Ø 66 x 200 mm	396 x 281 x 171 mm	50 x 38 x 28 mm	Ø 145 x 124 mm
Supported languages	English
Country of origin	China
Manufacturer / Brand	EBOLT	DAHUA	...	BCS View	...	Hikvision

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

SAP Code	300610259
Guarantee	2 years	2 years	...	3 years	2 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00