





	MOUNTING BRACKET FOR MOUNTING THE RECORDER IN THE RACK CABINET RM-1U-380 UNIVIEW	HUB USB 3.0 F7U-U3-CR-BP 1 m	RFID PROXIMITY KEY-FOB ATLO-504/B*P10	ACCESS CONTROLLER MODULE MC16-PAC-EX-3 ROGER
				
	59.86 DKK 59.86 DKK	104.05 DKK 104.05 DKK	14.75 DKK 14.75 DKK	5081.73 DKK 5081.73 DKK
Number of served transitions	3
Application	UNIVIEW recorders of the NVR302 series
Inputs	18
Outputs	12
In package	10 pcs The price for package	...
Number of users	max. 12000 - Number of identifiers
Standard	Unique EM 125kHz	...
Connectors	...	<ul style="list-style-type: none"> • 1 x Socket - micro USB 3.0 • 7 x socket - USB-A • 1 x Power socket - micro USB
Compatibility	EM4100/4102	...
Programming possibility	—	...
Number of media per ID	8 - Proximity card, PIN code, fingerprint, etc.
Length of the cable	...	1 m
Color	Black	...	Black	...
Number of permissions per ID	100
USB standard	...	3.0
Buffer memory	8 000 000 events buffer
MCT readers support	16 pcs
Readers connections	4 pcs - Wiegand / PRT
Number of login points	6
Number of access terminals	12
Number of access zones	6
Number of alarm zones	6
Number of automation nodes	6
Battery backup support	12 V / 7 Ah
Communication	<ul style="list-style-type: none"> • Ethernet - RJ-45 socket • RS-485 interface • RACS 5 v2 (Roger)

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Main features	...	<ul style="list-style-type: none"> • Solid workmanship • It can be used as a charger for multiple devices when connected to an external power source via the micro USB socket • LED indication • Transparent housing 	The TK-4100 chip	<ul style="list-style-type: none"> • Integrated support in VISO EX software • Functions in the VISO EX system: - MSSQL database - work in distributed systems - multi-station work - monitoring of transitions with video preview - T&A event reporting - maximum number of transitions in the system - unlimited - division of the system into partitions operated by independent operators - tool for integration with RACS5 (API) systems - integration with many systems (elevator systems, building applications, SMS, BMS, PSIM, VMS, Active Directory systems)
Power supply	...	5 V DC / 3 A (power adapter not included)	...	<ul style="list-style-type: none"> • 17 ... 22 V AC • 10 ... 15 V DC • 22 ... 26 V DC
Operation temp	5 °C ... 40 °C
Permissible relative humidity	10 % ... 95 % (non-condensing)
Weight	0.084 kg	0.050 kg	0.005 kg	0.14 kg
Dimensions	52 x 46.5 x 15 mm	135 x 35 x 19 mm	40 x 32 x 4 mm	175 x 72 x 30 mm
Manufacturer / Brand	UNIVIEW	ORICO	ATLO	ROGER
Guarantee	2 years	2 years	2 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00