

	VIDEO OVERVOLTAGE LIMITER OPV-4	ACCESS CONTROLLER ASC2104B-T DAHUA
		
	51.27 NOK 51.27 NOK	2218.02 NOK 2218.02 NOK
Number of served transitions	...	4 (two-way)
Support	...	DAHUA ASC2204C-H
Number of supported readers	...	4 pcs
Battery backup support	...	—
Output lines	...	5 pcs - Relay
Standard	<ul style="list-style-type: none"> • AHD - 5 Mpx • HD-CVI - 8 Mpx 4K UHD • HD-TVI - 5 Mpx NTSC • CVBS - PAL / NTSC 	...
Alarm inputs / outputs	...	1 / 1
Threshold voltage	> 2.4 V	...
Maximum stroke current	5 kA (8/20µs)	...
Protection level	700 V (1000V/uS)	...
Insertion loss	0.3 dB	...
Protect resistance	> 20 GΩ	...
Communication	...	<ul style="list-style-type: none"> • RS-485, • Wiegand 34/26, • Control panel CAN (Controler Area Network)
Response time	6.25 ns	...
Capacity	57 pF	...
Power supply	...	12 V DC / 1 A
Bandwidth	0 ... 160 MHz	...
Grounding	indirect, via Gas Spark Arrester and grounding bolt	...
Number of channels	4	...
Input socket type	BNC socket	...

Main features	...	<ul style="list-style-type: none"> • 20 000 indexed users • History of 30 000 events • Function to prevent of multiple use of the same code/card to gain access (anti-passback) • Door Left Open and Door Forced Open alarms • Watchdog built-in • Possibility to mount on a wall, or on the DIN TS-35 rail
Output socket type	BNC plug	...
Permissible relative humidity	...	max. 95 % (non-condensing)
Weight	0.16 kg	0.384 kg
Dimensions	117 x 30 x 80 mm	209 x 117 x 51 mm
Operation temp	-20 °C ... 50 °C	-30 °C ... 60 °C
Manufacturer / Brand	DELTA	DAHUA
Guarantee	3 years	3 years