



	SWITCH POE CS4220-16GT-135 16-PORT SFP DAHUA	INDOOR PANEL IP VTH5221D-S2 Wi-Fi / IP DAHUA
		
	5191.37 SEK 5191.37 SEK	3824.80 SEK 3824.80 SEK
Compatibility	...	Interphone installation - DAHUA IP
Shield	...	7 " capacitive touch screen
Resolution	...	1024 x 600
Internal memory	...	—
Memory card slot	...	Micro SD memory cards up to 32GB support (possible local recording), 8 GB included
LAN ports	<ul style="list-style-type: none"> • 16 x RJ45 10/100/1000 Base-T (2 x Hi-PoE (802.3bt) + 14 x PoE (802.3af/at)), • 2 x RJ45 10/100/1000 Base-T - Uplink, • 2 x SFP 1000 Base-X - Uplink 	...
Management	✓	...
LED diodes	Link, PoE, Power, System, 50 % PoE, 80 % PoE, 100 % PoE	...
Main features	...	<ul style="list-style-type: none"> • Wi-Fi Module, • Microphone built-in, • Speakers built-in, • Bidirectional communication, • Smooth adjustment of monitor parameters: image brightness, ring tone volume and conversation volume, • The ability to automatically take and save photos if you do not answer to the bell button, • The ability to record a short video message in the absence of a response to the bell button, • IP Dahua cameras support
Controlling	...	One-touch action buttons + capacitive touch screen

Alarm inputs	...	6
Alarm outputs	...	1
Transmission speed	<ul style="list-style-type: none"> • 10 / 100 / 1000 Mbps : 16 LAN & PoE ports, • 10 / 100 / 1000 Mbps : 2 RJ45 (Uplink) ports, • 1000 Mbps : 2 SFP (Uplink) ports 	...
Maximal output power	<ul style="list-style-type: none"> • 90 W / port Hi-PoE / PoE 802.3bt - 1, 2 ports • 30 W / port PoE 802.3af/at - 3 ... 16 ports 	...
Maximal total power	135 W	...
MAC addresses table	8k	...
Color	...	Black
Operation modes	<ul style="list-style-type: none"> • Long Distance PoE On : 250 m, 10 Mbps @ UTP cat. 5e, 6 	...
Supported languages	...	Polish, English, Bulgarian, Czech, Finnish, Slovak, Turkish, Hungarian
Main features	<ul style="list-style-type: none"> • Switch is managed through the web and the cloud (DoLynk Care application) • PoE power mode : The device supports 8-pin power supply - wires : 1-2(+), 3-6(-), 4-5(+), 7-8(-) • Intelligent management of Power Supply Unit power's output stage • protection against lightning discharges and voltage differences and strokes between devices • Watchdog PoE • Loop Protection • Compliance with the LLDP protocol • Spanning Tree STP/RSTP • Port Based VLAN : 32 • Data Flow Control (802.3x) • DHCP client • RESET button • Can be mounted in a Rack 19" cabinet 	...
Certificates	CE	...



Protections	<ul style="list-style-type: none"> • Protection against lightning discharges (common/differential) : 4 / 2 kV • Protection against electrostatic discharge - Contact/Air (ESD/EMP) : 6 / 8 kV 	...
Housing	Metal	...
Power supply	100 ... 240 V AC @ 47 ... 63 Hz	<ul style="list-style-type: none"> • 12 V DC / 580 mA, • PoE (802.3af)
Power consumption	max. 154 W	<ul style="list-style-type: none"> ≤ 7 W (operation) ≤ 1 W (standby)
Operation temp	-10 °C ... 55 °C	-10 °C ... 60 °C
Weight	2.29 kg	0.4 kg
Dimensions	440 x 220 x 44 mm, RACK 19", 1U	215 x 140 x 21 mm
Manufacturer / Brand	DAHUA	DAHUA
Guarantee	5 years	3 years