

	<a href="#">CONNECTOR FOR LED STRIPS AD-TL-6499/Z/T/RGB 10 mm ORNO</a>	<a href="#">POWER DISTRIBUTION UNIT AK-SP-05B AKYGA</a>	<a href="#">EXTENDER VGA-EX-30</a>
			
	0.98 EUR 0.98 EUR	9.03 EUR 9.03 EUR	42.31 EUR 42.31 EUR
Device type	...	...	Passive
Rated voltage	...	230 V AC / 50 Hz	...
Application	Works with LED lighting RGB	...	...
Power supply	...	...	—
Total maximal current	...	10 A	...
Strip width	10 mm	...	...
Video transmission range	...	...	max. 180 m
Symmetrical socket impedance	...	...	100 Ω
Maximal total load	...	2500 W	...
Response time	...	< 25 ns	...
Number of outlets	...	5 grounded outlets 10A/250V	...
"Index of Protection"	—	...	...
Maximal power voltage	48 V	...	...
Automatic delayed fuse	...	10 A / 250 V	...
Connectors type	...	...	<ul style="list-style-type: none"> <li>• 1 x VGA - Socket</li> <li>• 1 x RJ-45 - Socket</li> </ul>
Nominal voltage of surge suppressor	...	250 V / 50 Hz	...
DC filter to eliminate interferences	...	RFI ≤ 10 dB	...
Maximum stroke current	...	4,5 kA	...
Maximum energy absorption	...	150 J	...
Switch	...	with light indication	...
Length of the cable	...	3.0 m	...
Housing	...	Plastic (ABS)	...
Color	White	Black	...
Manufacturer / Brand	ORNO	AKYGA	...

Resolution	...	...	<ul style="list-style-type: none"> <li>• 1920 x 1200 px WUXGA @ 45 m (manufacturer data) @ 30 m (our tests result),</li> <li>• 1600 x 1200 px UXGA @ 45 m (manufacturer data) @ 30 m (our tests result),</li> <li>• 1280 x 1024 px SXGA @ 60 m (manufacturer data) @ 40 m (our tests result),</li> <li>• 1280 x 768 px WXGA @ 60 m (manufacturer data) @ 40 m (our tests result),</li> <li>• 1024 x 768 px XGA @ 75 m (manufacturer data) @ 50 (our tests result),</li> <li>• 800 x 600 px SVGA @ 120 m (manufacturer data) @ 80 m (our tests result),</li> <li>• 640 x 480 px VGA @ 180 m (manufacturer data) @ 120 m (our tests result)</li> </ul>
Bandwidth	...	...	≤ 60 MHz DC
Insertion loss	...	...	< 3 dB
Grounding	...	...	via grounding bolt
Operation temp	...	5 °C ... 50 °C	0 °C ... 55 °C
Permissible relative humidity	...	...	≤ 95 %
Weight	0.002 kg	0.372 kg	0.06 kg
Dimensions	30 x 20 mm	305 x 50 x 40 mm	64 x 61 x 25 mm
Guarantee	2 years	2 years	2 years