

	POWER DISTRIBUTION UNIT ACAR-DIGITAL (5 OUTLETS)	CONNECTOR FOR LED STRIPS AD-TL-6499/Z/T 8 mm ORNO	PROXIMITY CARD HOLDER CH-1
			
	55.52 EUR 55.52 EUR	0.89 EUR 0.89 EUR	0.70 EUR 0.70 EUR
Material	Plastic
Application	...	Works with LED lighting	...
Rated voltage	230 V AC / 50 Hz
Strip width	...	8 mm	...
Protection level	≤ 1.3 kV
Nominal load current	10 A (total)
Maximal load power	2300 W
"Index of Protection"	...	—	...
Maximal power voltage	...	48 V	...
Color	...	White	Colorless
Nominal stroke current	2 kA (L/N) - 8/20 μs
Maximum stroke current	6.5 kA (L/N) - 8/20 μs
Leak current	< 0.5 mA
Manufacturer / Brand	...	ORNO	ROGER
Automatic delayed fuse	✓
Response time	< 25 ns
Number of outlets	5 grounded outlets 16A/250V - (Schuko)
Switch	Two-way switch - with light indication
Main features	<ul style="list-style-type: none"> • Easily readable LCD with backlight displaying detailed information on system state, • Supply voltage measurement : 80 V ... 250 V @ 50Hz, • Supply current measurement : 0.01 A ... 10 A @ 50/60 Hz, • Power measurement : 1 W ... 2500 W, • Energy measurement : 1 Wh ... 9999 Wh • Energy meter reset • Setting the alarm after exceeding the power consumption
Length of the cable	3 m

Housing	Plastic - non-flammable
Weight	0.65 kg	0.002 kg	0.001 kg
Dimensions	447 x 57 x 43 mm	25 x 17 mm	96 x 63 x 4 mm
Guarantee	2 years	2 years	2 years