




	SWITCH POE IPB-5-10A-S4 5-PORT ATTE	SWITCH POE DS-3E0310HP-E 8-PORT Hikvision	SWITCH POE CS4006-4GT-60 4-PORT DAHUA
			
	78.56 EUR 78.56 EUR	139.81 EUR 139.81 EUR	141.51 EUR 141.51 EUR
LAN ports	<ul style="list-style-type: none"> • 1 x RJ45 10/100 Base-T - Uplink • 5 x RJ45 10/100 Base-T - PoE (802.3af/at) / Passive PoE 	<ul style="list-style-type: none"> • 2 x RJ45 10/100/1000 Base-TX - Uplink, • 8 x RJ45 10/100 Base-TX (1 x Hi-PoE (802.3af/at/bt) + 7 x PoE (802.3af/at)) 	<ul style="list-style-type: none"> • 4 x RJ45 10/100/1000 Base-T (1 x Hi-PoE + 3 x PoE (802.3af/at)), • 2 x RJ45 10/100/1000 Base-T - Uplink
Management	—	—	✓
Maximal output power	<ul style="list-style-type: none"> • 40 W @ Passive PoE - 1 ... 5 ports, • 30 W @ PoE (802.3at) - 1 ... 5 ports • 15.4 W @ PoE (802.3af) - 1 ... 5 ports 	...	<ul style="list-style-type: none"> • 60 W / port Hi-PoE - Port 1 • 30 W / port PoE 802.3af/at - 2 ... 4 ports
Transmission speed	10 / 100 Mbps : 1 Port LAN + 5 LAN & PoE ports	10 / 100 / 1000 Mbps : 2 LAN ports 10 / 100 Mbps : 8 LAN & PoE ports	<ul style="list-style-type: none"> • 10 / 100 / 1000 Mbps : 4 LAN & PoE ports, • 10 / 100 / 1000 Mbps : 2 Uplink ports
Maximal total power	90 W	110 W	60 W
MAC addresses table	...	16k	8k
LED diodes	Power, LAN	Power, PoE Max, PoE, Link/Act	Power, System, PoE, Link/Act
Operation modes	...	<ul style="list-style-type: none"> • Extend On : 150 m, 10 Mbps @ Hi-PoE (802.3bt) / 250 m, 10 Mbps @ PoE (802.3af/at) • Extend Off : 100 m, 100 Mbps @ Hi-PoE (802.3af/at/bt) 	Extend On : 250 m, 10 Mbps @ UTP cat. 5e, 6

Main features	<ul style="list-style-type: none"> • Supported PoE devices: 802.3af/at, Passive PoE • Possibility to connecting in cascade • Efficiency : 93 % @ 90 W • 5 polymer fuses - PoE • Possibility to power other devices powered from 55 V (screw connection) • PSU thermal protection • Short-circuit protection • Overload protection • The ability to independently turn on and off the PoE power for each of the LAN 1 ... LAN 4 ports • Switch has built-in a 55 V DC power supply adapter with power of 90 W • "Index of Protection" : IP55 	...	<ul style="list-style-type: none"> • Switch is managed through the web and the cloud (DoLynk Care application) • PoE power mode : The device supports 8-pin power supply - wires : 1-2(+), 3-6(-), 4-5(+), 7-8(-) • Intelligent management of Power Supply Unit power's output stage • protection against lightning discharges and voltage differences and strokes between devices • Watchdog PoE • Loop Protection • Compliance with the LLDP protocol • Port Based VLAN : 32 • Data Flow Control (802.3x) • DHCP client • RESET button • Kensington Lock • Possibility to mount to the wall
Certificates	...	CE	CE
SAP Code	...	301801346	...
Protections	<ul style="list-style-type: none"> • Protection against lightning discharges (common/differential) : 4 / 2 kV • Protection against electrostatic discharge - Contact/Air (ESD/EMP) : 6 / 8 kV
Housing	Desktop, Metal
Power supply	180 ... 240 V AC - Built-in switching power supply	48 V DC / 2.5 A (power adapter included)	53 V DC / 1.22 A (power adapter included)
Power consumption	max. 65 W
Operation temp	-10 °C ... 55 °C
Weight	0.43 kg	0.57 kg	0.3 kg
Dimensions	158 x 118 x 77 mm	218 x 107 x 28 mm	130 x 90 x 26 mm
Manufacturer / Brand	ATTE	Hikvision	DAHUA
Guarantee	3 years	3 years	3 years