



	IP CAMERA TC-C34XP SPEC:W/E/Y/2.8MM/V4.0 Color Maker - 4 Mpx 2.8 mm TIANDY	IP CAMERA APTI-501C2L-28WP Full- Color - 5 Mpx 2.8 mm
		
	189.54 EUR 189.54 EUR	75.91 EUR 75.91 EUR
Standard	IP	IP
Resolution	2592 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p	2592 x 1944 - 5 Mpx , 2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p
Sensor	1/2.8 " Progressive Scan CMOS	1/2.8 " SONY Starvis™ Back- illuminated CMOS
Lens	2.8 mm	2.8 mm
View angle	• 100 ° (manufacturer data) • 91 ° (our tests result)	93 °
White light LED illuminator range	15 m	30 m
Image compression method	S+265 / H.265 / H.264	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Network interface	...	10/100 Base-T (RJ-45)
Memory card slot	Micro SD card support up to 512GB	—
Alarm inputs / outputs	—	—
Main stream frame rate	25 fps @ 4 Mpx	25 fps @ 5 Mpx
Interface	10/100 Base-TX (RJ-45)	...
Audio	• Microphone built-in • Audio transmission via network	• Microphone built-in, • Audio transmission via network
WEB Server	Built-in	Built-in
Max. number of on-line users	2	10
ONVIF	✓	19.12
RS-485 interface	...	—
Mobile phones support	Port no.: 3000 or access by a cloud (P2P) • Android: Free application EasyLive Plus • iOS (iPhone): Free application EasyLive Plus	Port no.: 80 or access by a cloud (P2P) • Android: Free application BitVision • iOS (iPhone): Free application BitVision
Access from PC	Port no.: 3000 or access by a cloud (P2P) - PC: Free application Easy7 Smart Client Express	...

Default IP address	DHCP or 192.168.1.2	192.168.1.168
Default admin user / password	admin / - The administrator password should be set at the first start	admin / admin
Web browser access ports	80, 443, 3000, 3001, 3002, 23002	80
Mobile client access ports	3000, 3001	80
PC client access ports	3000, 3001	80
Port ONVIF	80	80
RTSP URL	...	rtsp://user:password@ip_address:80/0 - Main stream rtsp://user:password@ip_address:80/1 - Sub stream
Intelligent image analysis	<ul style="list-style-type: none"> crossing the line (tripwire) intrusion 	<ul style="list-style-type: none"> intrusion crossing the line (tripwire) loitering detection detection of people gathering vehicle detection
Main features	<ul style="list-style-type: none"> WDR - 120 dB - Wide Dynamic Range 3D-DNR - Digital Noise Reduction F-DNR (Defog) - Reduction of image noise caused by precipitation ROI - improve the quality of selected parts of image BLC/HLC - Back Light / High Light Compensation ICR - Movable InfraRed filter Day/night mode Motion Detection Privacy zones 	<ul style="list-style-type: none"> WDR - 120 dB - Wide Dynamic Range 3D-DNR - Digital Noise Reduction ROI - improve the quality of selected parts of image F-DNR (Defog) - Reduction of image noise caused by precipitation Flicker Control - The technology eliminates the tiring eyes flickering image effect BLC/HLC - Back Light / High Light Compensation Motion Detection Privacy zones Possibility to change the resolution, quality and bit rate Mirror - Mirror image Sharpness - sharper image outlines
Power supply	<ul style="list-style-type: none"> PoE (802.3af), 12 V / 590 mA 	<ul style="list-style-type: none"> PoE (802.3af), 12 V DC / 290 mA
Power consumption	≤ 7 W	≤ 3.5 W
Mechanical protection class	—	...
Housing	Dome - Metal + Plastic	Compact - Metal
Color	White	White
"Index of Protection"	IP66	IP67

Operation temp	-40 °C ... 65 °C	-20 °C ... 60 °C
Weight	0.33 kg	0.45 kg
Dimensions	Ø 117 x 96 mm	171 x 73 x 73 mm
Supported languages	Polish, English, Albanian, Arabic, Spanish, Korean, French, Dutch, Hebrew, German, Portuguese, Russian, Thai, Turkish, Ukrainian, Vietnamese, Italian	Polish, English, Bulgarian Czech, French, Spanish, Dutch, German, Portuguese, Russian, Turkish, Italian
Manufacturer / Brand	TIANDY	APTI
Guarantee	3 years	2 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00