

	BATTERY AKU- AA-2000/GC*P2 1.2 V Ni-MH HR6, AA Green Cell	NVR APTI-N3224AI-P24-I3 32 CHANNELS, 24 PoE	SWITCH POE GTX- CLM1-18-16G2G2SFP 16- PORT SFP	FOLDING STEEL MAST M-2.0SS/40 2 m
				
	3.89 EUR 3.89 EUR	432.24 EUR 432.24 EUR	283.93 EUR 283.93 EUR	16.48 EUR 16.48 EUR
Standard	...	TCP/IP
Height of the mast	2 m
Mast diameter	Ø 40 mm
Number of sections	1
Supported resolutions	...	max. 12 Mpx - 4000 x 3000 px
Wall thickness	1.5 mm
In package	2 pcs The price for package
Material	Steel
Rated voltage	1.2 V
Video outputs	...	1 pcs HDMI 4K 1 pcs VGA
Protection	Hot-dip galvanized
Battery capacity	2000 mAh
Possibility to combine to each other	✓
Battery type	Ni-MH
LAN ports	<ul style="list-style-type: none"> • 16 x RJ45 (16 x PoE (802.3af/at)), • 2 x RJ45 - Uplink • 2 x Port SFP - Uplink 	...
Management	✓	...
Size	HR6, AA
Audio support	...	<ul style="list-style-type: none"> • 32 Channels - Audio from cameras, • Bi-directional audio streaming support • Compliance with the AAC standard
Audio inputs	...	1 pcs CINCH
Audio outputs	...	1 pcs CINCH
LED diodes	Power, PoE, Link/Act, SYS	...
Image compression method	...	H.265+ / H.265 / H.264+ / H.264
Bitrate	...	320 Mbps
Supported hard drives	...	4 x 10 TB SATA
Recording modes	...	Manual, Sensor, Motion detection, Schedule

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

External storage devices backup	...	Records backup at (.avi) format to USB (pendrive)
Transmission speed	<ul style="list-style-type: none"> • 10 / 100 / 1000 Mbps : 16 x Port LAN & PoE • 10 / 100 / 1000 Mbps : 2 x LAN ports - Uplink • 1000 Mbps : 2 x Port SFP - Uplink 	...
Searching and playback the records	...	Records searching: timeline or file list. Playback: forward, fast Playback max. 16 cameras in the same time @ 1080p
Network interface	...	1 x RJ-45 10/100/1000 Base-TX
Network functions	...	Network Client Software and IE browser: live view, playback and backup of the records, configuration of the recorder parameters
Maximal output power	30 W / port PoE - 1 ... 16 ports	...
Maximal total power	280 W	...
Main features	<ul style="list-style-type: none"> • Loop Protection • Data Flow Control • VLAN support • QoS - mechanisms, which provide the high quality of transmission • RESET button • Can be mounted in a Rack cabinet 	...
Certificates	CE, FCC, RoHS	...
Protections	Overvoltage \pm 4 kV	...
Network protocols	...	IPv6, TCP/IP, HTTP, HTTPS, UPnP, DNS, NTP, SMTP, DHCP, FTP, DDNS, RTSP, RTCP, P2P, PPPoE
ONVIF	...	✓
Default IP address	...	192.168.1.88	192.168.2.1	...
Default admin user / password	...	admin / 12345	admin / admin	...
Web browser access ports	...	80, 5000, 554
PC client access ports	...	80, 5000, 554
Mobile phones support	...	Access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application BitVision, Android: Free application iVMS320 • Android: Free application BitVision, iOS: Free application iVMS320
USB	...	<ul style="list-style-type: none"> • 2 pcs USB 2.0 • 1 pcs USB 3.0
Serial ports	...	RS-485
Alarm inputs / outputs	...	16 / 4



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

PTZ control	...	<ul style="list-style-type: none"> • IP Speed Dome Cameras • RS-485 control
Motion Detection	...	Split the screen into zones : 22 x 18 motion zones
Intelligent image analysis	...	✓
Main features	...	<ul style="list-style-type: none"> • Support for intelligent image analysis, available in cameras from the APTI-AI series • D-ZOOM - Digital Zoom
Mouse support	...	✓
IR remote controller in the set	...	—
Switch PoE	...	24-port PoE Switch built-in : 15 W / Channel - PoE (802.3af)
Maximum total switch load	...	200 W
Power supply	...	100 ... 240 V AC, 50 / 60 Hz	100 ... 240 V AC	...
Power consumption	...	≤ 20 W (without HDD)
Operation temp	...	-10 °C ... 50 °C	-10 °C ... 45 °C	...
Weight	0.03 kg	4.75 kg	2.52 kg	3.05 kg
Dimensions	...	440 x 372 x 69 mm	440 x 215 x 45 mm, RACK 19", 1U	...
Supported languages	...	Polish, English, Czech, French, Greek, Spanish, Dutch, German, Portuguese, Russian, Ukrainian, Italian
Manufacturer / Brand	Green Cell	APTI	...	DELTA
Guarantee	2 years	2 years	2 years	4 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00