



	EXTENDER HDMI+USB-EX-100-4K-V2	AHD, PAL, TCP/IP DVR HYBRO-408 4 CHANNELS
		
	246.61 EUR 246.61 EUR	68.16 EUR 68.16 EUR
Standard	...	AHD, PAL, TCP/IP
Video inputs	...	4 pcs BNC - AHD, CVBS
Supported HDMI resolutions	480p, 576i, 576p, 720p 1080i, 1080p, 4K x 2K, 4K UHD	...
Video outputs	...	1 pcs HDMI 1 pcs VGA
Audio inputs	...	4 pcs CINCH
Audio outputs	...	1 pcs CINCH
Maximal transmission range	100 m UTP cat. 5e, 6 @ 4K UHD ,	...
Image compression method	...	H.264
Max. number of receivers working in the same time	253	...
Number of compression levels	...	6
Protocols	HDbiT	...
Main features	<ul style="list-style-type: none"> • Extender also allows to extend an USB 2.0 port, eg. in order to control the recorder using the mouse • Audio transmission via network 	...
Main features	<ul style="list-style-type: none"> • The devices do not require direct connection, they also operate via the LAN network • The need for a separate power supply for the transmitter and receiver 	...
Image records resolutions	...	AHD-NH (960 x 1080) AHD-M (1280 x 720) AHD-L, PAL (928 x 576) PAL (704 x 576) IP (1280 x 720) IP (1920 x 1080)
Operation temp	-20 °C ... 60 °C	...
Permissible relative humidity	0 % ... 90 % (non-condensing)	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Maximal total frame rate	...	AHD : 100 fps @ 960 x 1080 px, AHD : 100 fps @ 1280 x 720 px, AHD, PAL : 100 fps @ 928 x 576 px, AHD, PAL : 100 fps @ 704 x 576 px, IP : 200 fps @ 1920 x 1080 px, IP : 200 fps @ 1280 x 720 px
Recording speed adjustment	...	1 ... 25 fps @ 960 x 1080 px 1 ... 25 fps @ 1280 x 720 px 1 ... 25 fps @ 928 x 576 px 1 ... 25 fps @ 704 x 576 px for each channel
Operation modes	...	<ul style="list-style-type: none"> • 4 x AHD-NH • 4 x AHD-M • 4 x PAL • 2 x AHD-M + 2 x IP 720p • 8 x IP 720p • 8 x IP 1080p <p>The 4 x AHD-NH mode allows to combine the AHD-H, AHD-M, PAL cameras, eg.: 2 x AHD-H + 2 x AHD-M, 2 x AHD-H + 2 x PAL</p>
Recording modes	...	Manual, Motion Detection, Schedule
Supported hard drives	...	1 x 6 TB SATA
External storage devices backup	...	Records backup at (.avi) format to USB (pendrive)
Searching and playback the records	...	Records searching: timeline or file list. Playback: forward, fast, slow.
Network functions	...	Network Client software or IE browser: playback, DVR settings, files download, records searching
Mobile phones support	...	Port no.: 34567 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application XMEye • iOS (iPhone): Free application XMEye
Alarm inputs / outputs	...	—
PTZ control	...	RS-485 - PELCO-D/P
Motion Detection	...	Split the screen into zones : 16 x 12 motion zones
Mouse support	...	✓

IR remote controller in the set	...	—
Power supply	<ul style="list-style-type: none"> • Transmitter 5 V DC / 1 A (power adapter included) • Receiver 5 V / 1 A (power adapter included) 	12 V DC / 2.5 A (power adapter included)
Color	...	Black
Weight	0.31 kg	0.84 kg
Dimensions	133 x 90 x 26 mm - Transmitter or receiver dimensions	255 x 247 x 44 mm
Supported languages	...	English, Czech, French, Greek, Spanish, Dutch, German, Polish, Portuguese, Russian, Romanian, Slovak, Swedish, Turkish, Hungarian, Vietnamese, Italian
Country of origin	...	China
Guarantee	2 years	2 years