

	ACCESS CONTROLLER ASI3213G-MW DAHUA	CONTACTS CLEANING PREPARATION KONTAKT-S/400 SPRAY 400 ml AG TERMOPASTY
		
	495.91 EUR 495.91 EUR	6.70 EUR 6.70 EUR
Sensor	CMOS	...
Package	...	Spray 400 ml
Application	...	Cleaning and regeneration of contacts
Matrix size	2 Mpx	...
Main features	...	Spray preparation with a brush for easy application in hard-to-reach places
Resolution	1920 x 1080 - 1080p	...
Standard	TCP/IP	...
IR illuminator	✓	...
LED illuminator	✓	...
Temperature measurement	—	...
Temperature measurement range	—	...
Accuracy of temperature measurement	—	...
Face recognition distance	0.3 m ... 1.5 m (max 1500 faces in the database)	...
RFID proximity reader built-in	<ul style="list-style-type: none"> • 13.56 MHz S50 • Memory of 1500 RFID cards 	...
Internal memory	Support storage of 150 000 records	...
Video output	—	...
RS-485 interface	✓	...
RS-232 interface	—	...
Wiegand interface	—	...
USB	1 x USB 2.0	...
Memory card slot	—	...
Alarm inputs / outputs	1 / 1 - Relay outputs	...
Audio	Voice message	...
Network interface	1 x 10/100 Base-T (RJ-45)	...
Network protocols	IPv4, RTSP, RTP, TCP, UDP, P2P	...
WEB Server	Built-in	...
ONVIF	—	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Default IP address	192.168.1.108	...
Default admin user / password	admin / - The administrator password should be set at the first start	...
Web browser access ports	80, 37777	...
PC client access ports	37777	...
Main features	<ul style="list-style-type: none"> • Built-in LCD display showing the image from the video camera - 4.3 " capacitive touch screen, 480 x 272 px • Identification modes : PIN, Proximity identifier 13.56 MHz S50, Face recognition, Any combination of the above • 1500 users • Software update via network • Real-time Surveillance • Multiple Authentication • Take face image after swiping card • Auto-Registration • Backup to USB drive (pendrive, external drive) • Output button support • Door status detection • Lock control • Function to prevent of multiple use of the same code/card to gain access (anti-passback) • Auto-uploads alarm messages to Master or client station after entering the duress code to open the door • Ability to work with reed switch and signalling the door being opened too long • 128 General Purpose Schedules • Unlocking the transition only when more than one user is present • Tamper protections 	...
Power supply	12 V DC / 1.5 A (power adapter included)	...
Power consumption	≤ 18 W	...

Housing	Plastic (ABS)	...
Color	Black + Silver	...
"Index of Protection"	—	...
Operation temp	-10 °C ... 55 °C	...
Weight	<ul style="list-style-type: none"> • 0.22 kg (without stand) • 0.24 kg (with stand) 	0.36 kg
Dimensions	<ul style="list-style-type: none"> • 116 x 107 x 22 mm (without stand) • 116 x 107 x 78 mm (with stand) 	Ø 66 x 187 mm
Supported languages	English	...
Manufacturer / Brand	DAHUA	AG TERMOPASTY
Guarantee	3 years	...