



	SWITCH POE HS4408-4ET-96 4-PORT + 4 x SFP DAHUA	POWER DISTRIBUTION UNIT PR-1.5M-4G/B (4 OUTLETS) 1.3 m
		
	173.28 CAD 173.28 CAD	5.46 CAD 5.46 CAD
Rated voltage	...	220 ... 240 V AC / 50 Hz
Total maximal current	...	10 A
Maximal total load	...	2500 W
Number of outlets	...	4 grounded outlets 10A/250V CEE 7/5
Fuse	...	—
Switch	...	—
Wire gauge	...	3 x 1.5 mm ²
Length of the cable	...	1.3 m
Housing	...	Plastic
Color	...	Black
LAN ports	<ul style="list-style-type: none"> • 4 x RJ45 (10/100/1000 Base-T, 3 PoE (802.3af/at) + 1 PoE (802.3bt) / Hi-PoE / PoE (802.3af/at)) • 4 x Uplink (port SFP - 1000 Base-X) 	...
Transmission speed	<ul style="list-style-type: none"> • 10 / 100 LAN & PoE ports • 1000 SFP ports 	...
Management	✓	...
Maximal output power	<ul style="list-style-type: none"> • 30 W / port PoE 802.3af/at • 90 W / port PoE 802.3bt 	...
Maximal total power	96 W	...
Operation modes	<ul style="list-style-type: none"> • Extend On : 250 m, 10 Mbps • Extend Off : 100 m, 10 / 100 Mbps 	...

Main features	<ul style="list-style-type: none"> • DIN, TS-35 rail mounting • Data Flow Control • protection against lightning discharges and voltage differences and strokes between devices • Industrial wide temperature design. • Intelligent management of Power Supply Unit power's output stage • PoE (802.3af), PoE (802.3at), Hi-PoE, PoE (802.3bt) • PoE Watchdog / PD Alive mode - monitoring of the ports that power PoE devices and automatic restart by cutting off the power supply when an unresponsive device is detected • The ability to connect two power adapters - redundant power supply • The device supports 8-pin power supply 	...
LED diodes	Power, Link/Act, PoE	...
Certificates	CE	...
Power supply	48 ... 57 V DC (power adapter included)	...
Housing type	DIN	...
Operation temp	-30 °C ... 65 °C	...
Weight	0.618 kg	0.26 kg
Dimensions	150 x 110 x 42 mm	196 x 54 x 39 mm
Manufacturer / Brand	DAHUA	...
Guarantee	3 years	2 years