

	FLASHLIGHT LT-TACTICAL-TAC/700 ENERGIZER	IP CAMERA APTI-AI203PV21-28W - 1080p 2.8 mm
		
	12034.29 HUF 12034.29 HUF	12007.62 HUF 12007.62 HUF
Light source	3 pcs LED	...
Standard	...	TCP/IP
Sensor	...	1/2.9 " Progressive Scan CMOS
Matrix size	...	2.1 Mpx
Luminous flux	700 lm (high) , 100 lm (medium) , 20 lm (low)	...
Range	max. 100 m (high)	...
Resolution	...	1920 x 1080 - 1080p , 1280 x 720 - 720p
Battery power supply	Lithium batteries : 2 pcs CR123A 3 V (included)	...
Lens	...	2.8 mm
View angle	...	105 °
Range of IR illumination	...	30 m
Image compression method	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Alarm inputs / outputs	...	—
Audio	...	—
Main stream frame rate	...	25 fps @ 1080p
Network interface	...	10/100 Base-T (RJ-45)
WEB Server	...	Built-in - port 80
Max. number of on-line users	...	10
ONVIF	...	✓

Main features	<ul style="list-style-type: none"> • Backup time : 2 h (high) ... 30 h (low), • 4 light modes : High, Medium, Low, Stroboscopic mode, • Impact resistant up to 1 m, • Rear button for easy operation • Pivoting metal clip for belt, bag or shirt • Immunity to environmental changes • Waterproof • "Index of Protection" : IPX4 • Small dimensions 	...
Material	Aluminum	...
Main features	...	<ul style="list-style-type: none"> • Intelligent image analysis : intrusion, motion detection based on human detection • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • ROI - improve the quality of selected parts of image • Flicker Control - The technology eliminates the tiring eyes flickering image effect • Possibility to change the resolution, quality and bit rate • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • ICR - Movable InfraRed filter • Motion Detection • Privacy zones • Day/night mode • Auto White Balance • Mirror - Mirror image • RESET button - on the cable • Sharpness - sharper image outlines
Mobile phones support	...	Port no.: 80 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application BitVision • iOS (iPhone): Free application BitVision
Default IP address	...	192.168.1.168
Default admin user / password	...	admin / - The administrator password should be set at the first start

Web browser access ports	...	80
PC client access ports	...	80
Mobile client access ports	...	80
Port ONVIF	...	80
RTSP URL	...	rtsp://user:password@ip_address:80/0 - Main stream rtsp://user:password@ip_address:80/1 - Sub stream
Power supply	...	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 220 mA
Power consumption	...	≤ 2.7 W
Housing	...	Dome, Metal + Plastic
Vandal-proof	...	—
Color	Black	White
"Index of Protection"	...	IP65
Operation temp	...	-20 °C ... 60 °C
Weight	0.142 kg (total)	0.23 kg
Dimensions	33 x 35 x 121 mm	Ø 108 x 83 mm
Supported languages	...	Polish, English, Bulgarian, Czech, French, Spanish, Dutch, Portuguese, Russian, Turkish
Manufacturer / Brand	ENERGIZER	APTI
Guarantee	2 years	2 years