



	SWITCH POE DS-3E1510P-SI 8-PORT SFP Hikvision	WORK GLOVES WG-422/XL Bee-Smart WONDER GRIP
		
	198.66 CHF 198.66 CHF	4.55 CHF 4.55 CHF
Application	...	<ul style="list-style-type: none"> • Construction and public works, • Warehousing - packing and logistics, • DIY, • Assembly
Color	...	Black + Blue
LAN ports	<ul style="list-style-type: none"> • 8 x RJ45 10/100/1000 Base-T (8 x PoE (802.3af/at)), • 2 x port SFP 1000 Base-X 	...
Material	...	Polyester + latex coating (palm coated)
Transmission speed	<ul style="list-style-type: none"> • 10 / 100 / 1000 Mbps - 8 LAN & PoE ports, • 1000 Mbps - 2 SFP ports - Uplink 	...
Maximal output power	30 W / port PoE	...
Maximal total power	110 W	...
MAC addresses table	8k	...
Management	✓	...
Default IP address	192.168.1.64	...
Default admin user / password	admin / -	...
Supported norms	...	<ul style="list-style-type: none"> • EN 388:2016 - Mechanical protection 3131X • EN 407:2004 - Thermal protection X1XXXX
Size	...	10 / XL
Operation modes	<ul style="list-style-type: none"> • Extend On : 300 m, 10 Mbps • Extend Off : 100 m, 1000 Mbps 	...

Main features	<ul style="list-style-type: none"> • Switch is web managed • Configuration and management from the iVMS-4200 application • MDI/MDI-X auto detection feature - auto detecting the data transmission mode • View topology and network status • Data Flow Control • Storm Control function • Port mirroring function • Static link aggregation • QoS : Queue scheduling: SP, WRR, SP+WRR • VLAN support : 4094 • Port Isolation • Spanning Tree STP/RSTP • SNMPv1/v2c • Compliance with the LLDP protocol • Watchdog PoE • The device supports 8-pin power supply - wires : 1-2(-), 3-6(+), 4-5(+), 7-8(-) • Endspan mode support - wires : 1-2(-), 3-6(+) • Midspan mode support - wires : 4-5(+), 7-8(-) • Remote configuration • Remote update of software • System logs • Possibility to mount to the wall 	<ul style="list-style-type: none"> • Thermal protection : 100 °C (X1XXXX), • Ergonomics and comfort • High grip • Soft coating
LED diodes	Power, Link/Act, PoE, PoE Max, 9 SFP, 10 SFP	...
Certificates	CE, FCC, RoHS	...
Housing	Metal, Desktop	...
Protections	Overvoltage 6 kV - PoE ports	...
Power supply	48 V DC / 2.5 A (power adapter included)	...
Power consumption	max. 120 W	...
Operation temp	-10 °C ... 55 °C	...
Weight	0.57 kg	...
Dimensions	218 x 109 x 28 mm	...
Manufacturer / Brand	Hikvision	WONDER GRIP
SAP Code	301802029	...
Guarantee	3 years	...