



Image compression method	J204 + J205 / J206 + J207 / J208 + J209 / MJPEG	J202 / J203 + / J204 / J205 + / MJPEG	J204 / J205 +												
Network functions			Network Client Software and its browser, live view, playback and history of the configuration of the recorder parameters.												
Device		802.11G/11N													
Power supply distance		12 m per 120 W 1.2 per USB 3.0													
Power supply distance		12 m per 120 W 1.2 per USB 3.0													
Power supply distance		12 m per 120 W 1.2 per USB 3.0													
Maximum frame rate	30 fps @ 4 Meg 25 fps @ 2.5 Meg	25 fps - 1080p													
Maximum resolution		Max: 1080i/30 frames per sec in 2560K support (optional local recording)													
Network interface		10/100/1000 Mbps / RJ-45													
PTZ control															
Motion Detection															
Alarm support															
IP address resolution in the net															
Network protocols		HTTP, HTTPS, TCP/IP, UPnP, H.264, H.265, RTSP, RTMP, ONVIF, ONVIF, NTP, NTP, UPnP, PPTP, PPPoE, DNS, FTP, IP Filter, QoS, Bonjour, IEEE 802.1x													
Security of codes															
RTSP stream		Push in													
Maximum protection class															
Max. number of channels															
ONVIF															
Audio		2x 1W Microphone built-in. Audio output RF-emissional audio streaming support													
Mobile phones support		Net via 3777 or access by a cloud (P2P) Android: Free application <a href="#">iMMS Manager</a> iOS (iPhone): Free application <a href="#">iMMS Manager</a>													
Default admin user / password		admin / The administrator password should be set at the first start													
Default IP address		192.168.1.108													
Web browser access path		http://192.168.1.108													
PC client access path		192.168.1.108													
Mobile client access path		192.168.1.108													
Port ONVIF		80													
RTSP URL		rtsp://admin:admin@192.168.1.108:554/axis/cam/1-16andtype=1 Main stream rtsp://admin:admin@192.168.1.108:554/axis/cam/1-16andtype=1 Sub stream													
Main features		• WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • BLC - Back Light Compensation • EIS - Electronic Image Stabilization • Motion Detection Zones • AEC - Auto White Balance • AGC - Automatic Gain Control • AED - Anti-Electronic Disturbance • Day/Night mode • iC - Intelligent Privacy Zones • iS-2560K - High Frame Rate - 16 x													
Power supply	12 V DC / 150 mA	12 V DC / 150 mA	12 V DC / 150 mA												
Mounting	Wall, 2 x M6	Wall, 2 x M6	Wall, 2 x M6												
Material	ABS, PC	ABS, PC	ABS, PC												
Weight of Protection*	0.8 kg	0.8 kg	0.8 kg												
Operating temp.	0°C ~ 50°C	0°C ~ 50°C	0°C ~ 50°C												
Dimensions	44 x 35 x 23 mm 70 mm (total height)	44 x 35 x 23 mm 70 mm (total height)	44 x 35 x 23 mm 70 mm (total height)												
Supported languages	Polish, English, Czech, French, Spanish, Dutch, German, Portuguese, Russian, Ukrainian, Turkish, Chinese, Hungarian, Vietnamese, Italian	Polish, Polish	English, Polish												
Manufacturer / Brand	DELTA	DELTA	DELTA												
Connector	2 BNC	2 BNC	2 BNC												



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00