





	IP CAMERA TC-C35WQ SPEC:I5W/E/Y/2.8MM/V4.2 - 5 Mpx 2.8 TIANDY	ACCESS POINT +ROUTER ARCHER-VR400 VDSL / ADSL 300 Mbps + 867 Mbps	WORK GLOVES WG-422/XL Bee-Smart WONDER GRIP	WIRELESS DOOR CHIME ATLO-DB-2/RX AC 230V ATLO
				
	257.38 EUR 257.38 EUR	81.99 EUR 81.99 EUR	4.73 EUR 4.73 EUR	6.98 EUR 6.98 EUR
Support	ATLO-DB-2/TX
Standard	IP
Signaling mode	Optical - sound signaling
Number of ring-tones	60
Frequency range	...	• 2.4 GHz, • 5 GHz
Volume adjustment	0 ... 90 dB - 5-step
Application	<ul style="list-style-type: none"> • Construction and public works, • Warehousing - packing and logistics, • DIY, • Assembly 	...
Operation range	max. 150 m in open area
Frequency band	433 MHz
Material	Polyester + latex coating (palm coated)	...
Resolution	2880 x 1620 - 5 Mpx , 2688 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p
Standards	...	IEEE 802.11 b/g/n, IEEE 802.11 a/n/ac, IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, ITU G.993.2, ITU-T G.993.5 (G.vector), ITU-T G.998.4 (G.INP), Full-rate ANSI T1.413 Issue 2, ITU-T G.992.1(G.DMT), ITU-T G.992.2(G.Lite), ITU-T G.994.1 (G.hs), ITU-T G.995.1, ITU-T G.992.3 (G.DMT.bis), ITU-T G.992.4 (G.lite.bis), ITU-T G.992.5
Sensor	1/2.7 " Progressive Scan CMOS
Lens	2.8
View angle	104 °
Range of IR illumination	50 m
White light LED illuminator range	15 m
Memory card slot	Micro SD card support up to 512GB

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Supported norms	<ul style="list-style-type: none"> • EN 388:2016 - Mechanical protection 3131X • EN 407:2004 - Thermal protection X1XXXX 	...
LAN ports	...	3x RJ-45 (10/100 Mbps, Auto MDI/MDX) 1x RJ-45 (10/100/1000 Mbps, Auto MDI/MDX)
Image compression method	S+265 / H.265 / H.264
Size	10 / XL	...
WAN interface	...	1x RJ-11, ADSL / ADSL2 / ADSL2+ / VDSL / VDSL2
Alarm inputs / outputs	1 / 1
Transmitter power	...	< 20 dBm @ 2.4 GHz , < 23 dBm @ 5 GHz
Audio	<ul style="list-style-type: none"> • Microphone built-in, • Speaker built-in • Audio input • Audio output • Bi-directional audio streaming support • Audio transmission via network
Baud rates	...	300 Mbps @ 2.4 GHz + 867 Mbps @ 5 GHz
DHCP server	...	✓
Firmware update	...	✓
Main stream frame rate	<ul style="list-style-type: none"> • 25 fps @ 5 Mpx • 50 fps @ 2 Mpx
DDNS	...	✓
Interface	10/100 Base-TX (RJ-45)
WEB Server	Built-in
Max. number of on-line users	2
ONVIF	✓
Mobile phones support	Port no.: 3000 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application EasyLive Plus • iOS (iPhone): Free application EasyLive Plus
Access from PC	Port no.: 3000 or access by a cloud (P2P) - PC: Free application Easy7 Smart Client Express
Protections	...	<ul style="list-style-type: none"> • LAN : Firewall, MAC addresses filtering, IP addresses filtering, parental control, LAN ACL • WLAN : WEP 64/128-bit, WPA-PSK/WPA2-PSK, TKIP/AES
Default IP address	192.168.1.2
Management interface	...	Web browser



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Default admin user / password	admin / - The administrator password should be set at the first start
Web browser access ports	80, 443, 3000, 3001, 3002, 23002
Mobile client access ports	3000, 3001
PC client access ports	3000, 3001
Port ONVIF	80
Intelligent image analysis	<ul style="list-style-type: none"> • classification of people and vehicles • crossing the line (tripwire) • video tampering
Main features	...	<ul style="list-style-type: none"> • Firewall • Internet access filtering • Static / dynamic routing • Built-in 4-port switch • Wireless transmission statistics • The WPS function allows to easy establish an encrypted connection • QoS • WMM (Wi-Fi Multimedia) • Rate limit • Access control • Remote management • DMZ • parental control • Guest Network - a separate and secure network for guests • 1 x Port USB 2.0 • The DSL line splitter included 	<ul style="list-style-type: none"> • Thermal protection : 100 °C (X1XXXX), • Ergonomics and comfort • High grip • Soft coating 	The number of cooperated doorbell buttons (transmitters) can be increased as required
Operation temp	...	0 °C ... 40 °C
Permissible relative humidity	...	max. 90 % (max)



Main features	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • ROI - improve the quality of selected parts of image • NAS - Network Attached Storage support - allows to connect memory resources directly to the computer network • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • BLC/HLC - Back Light / High Light Compensation • Early Warning (EW) - combination of white light warning with audio signals • ICR - Movable InfraRed filter • Day/night mode • Possibility to change the resolution, quality and bit rate • Audio detection
Power supply	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 670 mA 	12 V DC / 1.5 A (power adapter included)	...	230 V AC
Power consumption	≤ 8 W
Housing	Compact - Metal
Color	White	...	Black + Blue	...
"Index of Protection"	IP67
Mechanical protection class	—
Operation temp	-40 °C ... 65 °C
Weight	0.52 kg	0.32 kg	...	0.06 kg
Dimensions	170 x 71 x 71 mm	216 x 125 x 32 mm	...	95 x 68 x 65 mm
Supported languages	Polish, English, Spanish, Korean, Italian, Turkish, Russian, Thai, French, Dutch, Hebrew, Arabic, Vietnamese, German, Ukrainian, Portuguese, Albanian
Manufacturer / Brand	TIANDY	TP-LINK	WONDER GRIP	ATLO
Guarantee	3 years	2 years	...	2 years