

	EXTENDER HDMI+USB-EX-100-4K	EXTENDER RECEIVER HDMI+USB-EX-100/RX SIGNAL	CURRENT TRANSFORMER SC-16 ZAMEL
			
	205.32 EUR 205.32 EUR	51.96 EUR 51.96 EUR	15.16 EUR 15.16 EUR
Device type	...	Receiver	...
Support	MEW-01
Maximum continuous primary current	100 A
Gear	3000 : 1
Frequency range	50/60 Hz
Supported HDMI resolutions	480p, 576i, 576p, 720p 1080i, 1080p, 4K x 2K, 4K UHD	480i, 480p, 576i, 576p, 720p, 1080i, 1080p	...
Wire gauge	16 mm (max)
Protocols	...	HDBiT	...
Maximal transmission range	<ul style="list-style-type: none"> • 70 m UTP cat. 6 @ 4K UHD, • 70 m UTP cat. 5, 5e @ 1080p • 50 m UTP cat. 5e @ 4K UHD (our tests result) 	100 m UTP cat. 5e, 6	...
Main features	<ul style="list-style-type: none"> • Extender also allows to extend an USB 2.0 port, eg. in order to control the recorder using the mouse 	<ul style="list-style-type: none"> • Extender also allows to extend an USB 2.0 port, eg. in order to control the recorder using the mouse • The devices do not require direct connection, they also operate via the LAN network • Audio transmission via network 	...
Main features	<ul style="list-style-type: none"> • Very good image quality with no visible distortions caused by compression • No delays in video transmission • No delays in mouse control operations • Transition of the HDMI signal in the transmitter • S/PDIF output 	...	Openable core
Manufacturer / Brand	...	SIGNAL	ZAMEL
Power supply	<ul style="list-style-type: none"> • Transmitter 5 V DC / 2 A (power adapter included) • Receiver 5 V / 2 A (power adapter included) 	5 V DC / 1 A (power adapter included)	...

Operation temp	-20 °C ... 60 °C	-10 °C ... 60 °C	-15 °C ... 60 °C
Permissible relative humidity	0 % ... 90 % (non-condensing)	20 % ... 90 % (non-condensing)	...
Weight	0.29 kg	0.168 kg	0.09 kg
Dimensions	150 x 107 x 28 mm - Transmitter or receiver dimensions	110 x 89 x 26 mm	45 x 34 x 31
Guarantee	2 years	2 years	2 years