






	SMART SWITCH SWITCHBOX-LIGHT/BLEBOX Wi-Fi, 230 V AC	SMART PROXIMITY LED LIGHT CONTROLLER PROXIDIMMER/BLEOX 12 ... 24 V DC	SMART LIGHTING DIMMER DIMMERBOX-V2/BLEBOX Wi-Fi, 230 V AC	LED AMPLIFIER AMPBOX/BLEBOX 12 ... 24 V DC	SMART LED LIGHTING CONTROLLER WLIGHTBOX-PRO/BLEBOX Wi-Fi, 12 ... 24 V DC
					
	103.25 PLN 103.25 PLN	56.10 PLN 56.10 PLN	169.92 PLN 169.92 PLN	72.40 PLN 72.40 PLN	161.79 PLN 161.79 PLN
Application	switching devices on/off	Touchless lighting control	lighting brightness control	<ul style="list-style-type: none"> Works with LED controllers : WLIGHTBOX-V3/BLEBOX, WLIGHTBOX-S-V2/BLEBOX, REFLECTIVE-SWITCH/BLEBOX, TWILIGHT-SWITCH/BLEBOX, PROXIDIMMER/BLEBOX, Works with LED lighting - (RGB/RGBW/CCT/MONO) 12-24V LED strips 	Works with LED lighting - (RGB/RGBW/RGBCCCT/CCT/MONO) 12-24V LED strips
Rated voltage	230 V AC	12 ... 24 V DC	230 V AC	12 ... 24 V DC	12 ... 24 V DC
Maximal total load	1150 W / 1150 VA	120 W	<ul style="list-style-type: none"> 250 W (resistance load), 30 W (inductive or capacitive load - e.g. LED lamp) 	480 W	288 W
Total maximal current	5 A	5 A	1.1 A	20 A (5 A / Channel)	12 A (3 A / Channel)
Number of inputs	1	0	2	4	1
Number of outputs	1	1	1	4	4
Connector type	screw terminals	screw terminals	screw terminals	screw terminals	screw terminals
Wireless	Wi-Fi, 2.4 GHz - IEEE 802.11g	—	Wi-Fi, 2.4 GHz - IEEE 802.11g	—	Wi-Fi, 2.4 GHz - IEEE 802.11g
Mobile phones support	<ul style="list-style-type: none"> The wBox free application on Android The wBox free application on iOS 	—	<ul style="list-style-type: none"> The wBox free application on Android The wBox free application on iOS 	—	<ul style="list-style-type: none"> The wBox free application on Android The wBox free application on iOS
Main features	<ul style="list-style-type: none"> Local control by physical button, schedule, timer, remote access, voice control, The ability to set the default status of the device after a power failure, µWiFi technology support 	<ul style="list-style-type: none"> Non-contact switching on and off, lighting brightness control, Detection range : 7 cm Possibility to hide the sensor Automatic calibration LED indication 	<ul style="list-style-type: none"> Local control by physical button, schedule, timer, remote access, voice control, The ability to set the default status of the device after a power failure, µWiFi technology support 	<ul style="list-style-type: none"> High power - max. 480 W, Digital signal enhancement, Signal correction : digital, Protections : optical isolation, Powerful and high performance, Small dimensions 	<ul style="list-style-type: none"> Local control by physical button, schedule, timer, sunrise and sunset mode, remote access, voice control, Controlling the color, color temperature, brightness, effect, changing time allows any interior arrangement predefined effects, effects modification, Operation modes : <ul style="list-style-type: none"> - 1 x RGB (color) - 1 x RGBW (color + white - brightness control) - 1 x RGB (color) + 1 x MONO (white) - 1 x CCT (white - brightness and color temperature control) - 2 x CCT (white - brightness and color temperature control) - 4 x MONO (single color) / halogen bulb Omnidirectional antenna Wi-Fi 5 dB, SMA-RP socket µWiFi technology support
Housing	Plastic	Plastic	Plastic	Plastic	<ul style="list-style-type: none"> Non-halogen plastic, Self-extinguishing Waterproof, Weatherproof
"Index of Protection"	IP20	IP20	IP20	IP20	IP54
Color	Black	Black	Black	Black	Black
Operation temp	-20 °C ... 50 °C	-20 °C ... 50 °C	-20 °C ... 50 °C	-20 °C ... 50 °C	-20 °C ... 50 °C
Weight	0.027 kg	0.02 kg	0.04 kg	0.036 kg	0.1 kg

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Dimensions	38 x 25 x 23 mm	39 x 39 x 16 mm	41 x 39 x 24 mm	48 x 39 x 18 mm	<ul style="list-style-type: none"> • 92 x 52 x 28 mm - without antenna • 230 x 85 x 28 mm - with antenna, vertical • 197 mm - Antenna
Manufacturer / Brand	BleBox	BleBox	BleBox	BleBox	BleBox
Guarantee	2 years	2 years	2 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00