



	VIDEO DOORPHONE S1401D VIDOS	SWITCH POE SPS-2P/1SFP 2-PORT + SFP
		
	4234.79 CZK 4234.79 CZK	1248.64 CZK 1248.64 CZK
Compatibility	VIDOS DUO	...
LAN ports	...	2 x RJ45, PoE (802.3af/at)
Sensor	1/2.7 ", 2.0 Mpx	...
View angle	170 °	...
IR illuminator	—	...
LED illuminator	✓	...
Fingerprint reader built-in	—	...
proximity reader built-in	—	...
Built-in keypad	✓	...
Management	...	—
The number of subscribers served	1	...
Video output	compatible with the VIDOS DUO digital video doorphone system	...
LED diodes	...	PWR - Power, FL - Link/Act port SFP, Speed - 1000 Mbps, Link/Act
Transmission speed	...	1 port SFP : 1000 Mbps + 2 LAN & PoE ports : 10 / 100 / 1000 Mbps
Maximal output power	...	25.5 W / port PoE
Maximal total power	...	51 W

Main features	<ul style="list-style-type: none"> • Fisheye lens • Wiring - 2 wires without polarity • Relay output : 1 pcs or 2 pcs - B5 Module • Support up to 12 indoor devices (monitors / uniphones) • Touch control keys • Illuminated buttons and signboard for the surname • PIR detectors support • Permanent or cyclical zoom-up of the observed image • Electric strikes and electromagnetic locks support • Electric lock supply: 12V DC / max. 300mA • Call start and lock opening indicator 	...
MAC addresses table	...	1k
Certificates	...	CE
Power consumption	<ul style="list-style-type: none"> ≤ 3 W (operation) ≤ 0.8 W (Standby mode) 	...
Power supply	24 V DC	52 V DC / 1.25 A (power adapter included) (2.5/5.5mm socket)
Housing	Acid-proof steel, Waterproof	...
Color	Silver	...
"Index of Protection"	IP54	...
Permissible relative humidity	...	10 % ... 90 %
Operation temp	-18 °C ... 55 °C	-20 °C ... 70 °C
Weight	0.7 kg	0.13 kg
Dimensions	220 x 120 x 50 mm	97 x 71 x 27 mm
Manufacturer / Brand	VIDOS	...
Guarantee	3 years	2 years