




	<a href="#">POWER SUPPLY ADAPTER ZR48-158/R10 48 V DC 3.3 A</a>	<a href="#">CABLE MANAGER TRSH-8-G*P10</a>	<a href="#">CABLE MANAGER OKR-40X40</a>
			
	23143.27 HUF 23143.27 HUF	538.46 HUF 538.46 HUF	419.23 HUF 419.23 HUF
Adapter type	Switching	...	...
In package	...	<b>10 pcs The price for package</b>	...
Hole diameter	...	Ø 8 mm	...
Assembly	...	The bottom layer is equipped with a Scotch tape	...
Power voltage	selectable by switch • 90 V ... 132 V AC, • 180 V ... 264 V AC	...	...
Color	...	Green	Silver
Material	...	Plastic	Steel galvanized
Voltage frequency range	47 ... 63 Hz	...	...
Output power	160 W	...	...
Output voltage	48 V DC	...	...
Output voltage adjustment	45.6 V ... 52.8 V DC	...	...
Maximal load	3.3 A	...	...
Efficiency	89 %	...	...
MTBF (Mean Time Between Faults)	> 700000 h - Telcordia SR-332	...	...
Manufacturer / Brand	DELTA	...	...
Protections	• Overvoltage • Short-circuit • Overload	...	...
Housing type	1 U Rack 10"	...	...
Operation temp. / Relative humidity	-10 °C ... 70 °C / 10 % ... 80 %	...	...
Weight	0.57 kg	...	...
Dimensions	256 x 44 x 99 mm	...	50 x 40 x 40 mm (opening for cables entry)
Guarantee	5 years	2 years	2 years