



	WIRELESS TRANSMISSION KIT AHD-M 5.8 GHz AV-300AHD-MINI TXRX SET	MOUNTING PROFILE USP-SM-1100 FOR SOLAR PANELS
		
	156.43 EUR 156.43 EUR	13.87 EUR 13.87 EUR
Number of channels	8	...
Material	...	Aluminum
Frequency range	5.610 ... 5.855 GHz The channels list Ch 1 = 5.855 GHz Ch 2 = 5.820 GHz Ch 3 = 5.780 GHz Ch 4 = 5.745 GHz Ch 5 = 5.715 GHz Ch 6 = 5.680 GHz Ch 7 = 5.645 GHz Ch 8 = 5.610 GHz	...
Video format	<ul style="list-style-type: none"> • AHD-M, • AHD-L, • PAL 	...
Audio frequency response	—	...
Transmitter power	20 dBm	...
Receiver sensitivity	-80 dBm	...
Radio communication range (at open area)	300 m	...
S/N ratio:	40 dB	...
Modulation	FM	...
Connectors	75 Ω	...
Power supply	<ul style="list-style-type: none"> • 9 V ... 24 V AC/DC, 240 mA - Transmitter • 9 V ... 24 V AC/DC, 130 mA - Receiver 	...
Protection	Overvoltage : 600 W - Video, 600 V - Power supply	...
Main features	<ul style="list-style-type: none"> • Real time transmission, with no delays nor loss of image quality • interference free transmission (industrial, 802.11, Bluetooth, radiotelephony, etc.) • High gain directional antennas providing stable operation 	...
"Index of Protection"	IP65	...

Operation temp	-20 °C ... 40 °C	...
Weight	<ul style="list-style-type: none"> • 0.264 kg - Transmitter • 0.270 kg - Receiver 	0.21 kg
Dimensions	78 x 118 x 79 mm - Transmitter or receiver dimensions	1100 x 50 x 50 mm
Guarantee	2 years	2 years