



	EXPANSION PLUG JPK-12X160/M5 EBOLT	AHD, HD-CVI, HD-TVI, PAL CAMERA BCS-EA48VWR6 - 8.3 Mpx 2.7 ... 13.5 mm - MOTOZOOM
		
	1.65 EUR 1.65 EUR	127.68 EUR 127.68 EUR
Standard	...	AHD, HD-CVI, HD-TVI, CVBS
Sensor	...	1/2.7 " Progressive Scan CMOS
Matrix size	...	8.3 Mpx
Material	<ul style="list-style-type: none"> • Expansion plug, Polypropylene • Screw, Steel galvanized • mounting screw, Steel galvanized 	...
Drilling diameter	12 mm	...
Expansion plug length	155 mm	...
Screw dimensions	Ø 8 x 160 mm, Internal thread M5	...
Screw	Ø 5 x 16 mm	...
Application	for Styrofoam 100 mm	...
Resolution	...	<ul style="list-style-type: none"> • AHD / HD-CVI / HD-TVI : 3840 x 2160 - 8.3 Mpx, 4K UHD 2592 x 1944 - 5 Mpx 2560 x 1440 - 3.7 Mpx • CVBS : 960 x 576 - 960H
Lens	...	2.7 ... 13.5 mm - Motozoom - AutoFocus
View angle	...	<ul style="list-style-type: none"> • 105 ° ... 33 ° (manufacturer data) • 96 ° ... 33 ° (our tests result)
Range of IR illumination	...	60 m
IR illuminator support	...	ICR - Movable InfraRed filter
IR illuminator power adjustment	...	Automatic
Video output	...	AHD / HD-CVI / HD-TVI / CVBS - 1 Vpp / 75 Ω

Audio	...	<ul style="list-style-type: none"> • Microphone built-in - HD-CVI only
Main features	...	<ul style="list-style-type: none"> • Motozoom lens • WDR - 120 dB - Wide Dynamic Range • 2D-DNR, 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • BLC/HLC - Back Light / High Light Compensation • Day/night mode • ICR - Movable InfraRed filter • Auto White Balance • AGC - Automatic Gain Control • Mirror - Mirror image • Sharpness - sharper image outlines
OSD menu	...	OSD menu available via recorder
Power supply	...	12 V DC / 660 mA
Power consumption	...	≤ 8 W
Housing	...	Dome, Metal
Color	...	White
Vandal-proof	...	—
"Index of Protection"	...	IP67
Operation temp	...	-30 °C ... 60 °C
Weight	...	0.6 kg
Dimensions	...	Ø 122 x 104 mm
Manufacturer / Brand	EBOLT	BCS UNIVERSAL
Guarantee	2 years	3 years