





	CONVERTER MODULE PZU-3509-W4 DC/DC	TV OR MONITOR MOUNT BRATECK-LCD-142A	TV OR MONITOR MOUNT BRATECK-PLB-6N	TV OR MONITOR MOUNT BRATECK-LPA39-223	ACCESS CONTROLLER ASI3213G-MW DAHUA	SET OF UTP / 2-WIRE CONVERTERS FOR LAN+POE TRANSMISSION ETH10-2WIRE.SET 2 PCS SET ATTE	EXTENDER ETHERNET+PoE LR1002-1ET-TRANSMITTER DAHUA
							
	10.76 EUR 10.76 EUR	16.01 EUR 16.01 EUR	16.30 EUR 16.30 EUR	15.68 EUR 15.68 EUR	500.45 EUR 500.45 EUR	89.51 EUR 89.51 EUR	52.88 EUR 52.88 EUR
Type	Increasing the voltage, DC/DC	...	...	...	...	...	...
Transmission ports	...	...	...	...	...	...	1 pcs BNC
Sensor	...	...	...	...	CMOS	...	...
Matrix size	...	...	...	...	2 Mpx	...	...
Number of inputs	2 - closed	...	...	...	...	...	...
Number of outputs	2 - closed	...	...	...	...	...	...
Resolution	...	...	...	...	1920 x 1080 - 1080p	...	...
Power voltage	5 ... 32 V DC	...	...	...	...	...	...
Connectors	...	...	...	...	...	• 1 pcs RJ45 • 1 pcs terminals (screw terminals) - 0.32 ... 3.3 mm <sup>2</sup> ( 22 ... 12 AWG )	...
Mounting standard	...	VESA 75, 100, 150, 200, 200x100	VESA 75, 100, 150, 200, 200x100, 300, 400, 400x200	VESA 75, 100, 200x100, 200	...	...	...
Output voltage	5 ... 35 V DC	...	...	...	...	...	...
LAN ports	...	...	...	...	...	1 pcs RJ45 10 Mbps	1 pcs RJ45
Output voltage adjustment	Multi-turn precision potentiometer adjustment (27 rotations)	...	...	...	...	...	...
Screen size range	...	17 " ... 37 "	26 " ... 47 "	23 " ... 42 "	...	...	...
Output current	2 A (max)	...	...	...	...	...	...
Bearing capacity	...	20 kg	75 kg	35 kg	...	...	...
Power	24 W (max)	...	...	...	...	...	...
Distance from mounting surface	...	70 ... 250 mm from wall	77 mm	45 ... 508 mm	...	...	...
Minimal voltage difference between out and in	0 V	...	...	...	...	...	...
Tilt adjustment	...	-15 ° ... 15 °	-15 ° ... 15 °	-15 ° ... 10 °	...	...	...
Standard	...	...	...	...	TCP/IP	...	...
Horizontal rotation	...	Articulated arm with two swivels in range -90 ° ... 90 ° each	...	-90 ° ... 90 °	...	...	...
IR illuminator	...	...	...	...	✓	...	...
Rotation in the plane of the screen	...	360 °	...	± 3 °	...	...	...
LED illuminator	...	...	...	...	✓	...	...
Temperature measurement	...	...	...	...	—	...	...
Temperature measurement range	...	...	...	...	—	...	...
Accuracy of temperature measurement	...	...	...	...	—	...	...
Application	• to cameras powering • to cameras with thermostat powering	...	...	...	...	...	...
Face recognition distance	...	...	...	...	0.3 m ... 1.5 m (max 1500 faces in the database)	...	...
RFID proximity reader built- in	...	...	...	...	• 13.56 MHz S50 • Memory of 1500 RFID cards	...	...
Internal memory	...	...	...	...	Support storage of 150 000 records	...	...
Video output	...	...	...	...	—	...	...
RS-485 interface	...	...	...	...	✓	...	...
RS-232 interface	...	...	...	...	—	...	...
Wiegand interface	...	...	...	...	—	...	...
USB	...	...	...	...	1 x USB 2.0	...	...
Memory card slot	...	...	...	...	—	...	...
Connectors description	...	...	...	...	...	ETH10-2WIRE-TX : • PoE IN - Passive PoE ≤ 30 W, PoE (802.3at) ≤ 30 W, PoE (802.3af) ≤ 15 W (*+/-: 1, 2 pins; +/-: 3, 6 pins) or (*+/-: 4, 5 pins; +/-: 7, 8 pins) • Power • DATA - 2-wire ETH10-2WIRE-RX : • PoE OUT - Passive PoE (*+/-: 4, 5 pins; +/-: 7, 8 pins) • Power • DATA - 2-wire	...
Transmission speed	...	...	...	...	...	10 Mbps	10 / 100 Mbps Full Duplex
Alarm inputs / outputs	...	...	...	...	1 / 1 - Relay outputs	...	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Audio	...	...	...	...	Voice message	...	...
Network interface	...	...	...	...	1 x 10/100 Base-T (RJ-45)	...	...
Network protocols	...	...	...	...	IPv4, RTSP, RTP, TCP, UDP, P2P	...	...
Transmission range	...	...	...	...	...	<ul style="list-style-type: none"> <li>• 1000 m @ 2-wire</li> <li>• 100 m @ UTP : Switch PoE</li> <li>• ETH10-2WIRE-TX</li> <li>• 100 m @ UTP :</li> <li>• ETH10-2WIRE-RX - IP Camera</li> </ul>	<ul style="list-style-type: none"> <li>max. 1000 m @ 10 Mbps</li> <li>max. 400 m @ 100 Mbps</li> <li>The range of data transfer and power supply is strongly dependent on the cable used and the power required to supply the receiver</li> </ul>
WEB Server	...	...	...	...	Built-in	...	...
ONVIF	...	...	...	...	—	...	...
LED indicators	...	...	...	...	...	<ul style="list-style-type: none"> <li>• Power</li> <li>• LAN</li> <li>• 2-wire</li> </ul>	...
Default IP address	...	...	...	...	192.168.1.108	...	...
Default admin user / password	...	...	...	...	admin / - The administrator password should be set at the first start	...	...
Web browser access ports	...	...	...	...	80, 37777	...	...
PC client access ports	...	...	...	...	37777	...	...
Protections	<ul style="list-style-type: none"> <li>• Short-circuit</li> <li>• Overheat</li> <li>• Reverse polarity connection</li> </ul>	...	...	...	...	<ul style="list-style-type: none"> <li>• Overvoltage - LAN, DATA</li> <li>• Protection against reverse polarity connection - Power</li> <li>• Overload 0.6 A - PoE IN</li> <li>• ETH10-2WIRE-TX</li> </ul>	Overvoltage
Main features	LED indication - Input voltage, Output voltage	...	...	...	...	<ul style="list-style-type: none"> <li>• Plug &amp; Play</li> <li>• Support for IP cameras and network devices</li> <li>• Full transparency for networks</li> <li>• Operation modes - Set with jumpers</li> </ul>	<ul style="list-style-type: none"> <li>• Plug &amp; Play</li> <li>• MDI/MDI-X auto detection feature - auto detecting the data transmission mode</li> <li>• Support for IP cameras and network devices</li> <li>• Easy installation - doesn't require any configuration of IP nor MAC address</li> <li>• The device operates from the camera side</li> <li>• Possibility to mount on a wall, or on the DIN TS-35 rail</li> <li>• UTP cable length to the camera max. 2 m</li> </ul>
Main features	...	...	...	...	<ul style="list-style-type: none"> <li>• Built-in LCD display showing the image from the video camera - 4.3" capacitive touch screen, 480 x 272 px</li> <li>• Identification modes : PIN, Proximity identifier 13.56 MHz S50, Face recognition, Any combination of the above</li> <li>• 1500 users</li> <li>• Software update via network</li> <li>• Real-time Surveillance</li> <li>• Multiple Authentication</li> <li>• Take face image after swiping card</li> <li>• Auto-Registration</li> <li>• Backup to USB drive (pendrive, external drive)</li> <li>• Output button support</li> <li>• Door status detection</li> <li>• Lock control</li> <li>• Function to prevent of multiple use of the same code/card to gain access (anti-passback)</li> <li>• Auto-uploads alarm messages to Master or client station after entering the duress code to open the door</li> <li>• Ability to work with reed switch and signalling the door being opened too long</li> <li>• 128 General Purpose Schedules</li> <li>• Unlocking the transition only when more than one user is present</li> <li>• Tamper protections</li> </ul>	...	

Power supply	...	...	...	...	12 V DC / 1.5 A (power adapter included)	ETH10-2WIRE-TX : • 30 ... 56 V DC - PoE • 10 ... 56 V DC - Power ETH10-2WIRE-RX : • 10 ... 56 V - Power • The output PoE voltage is equal to the input voltage	• ePoE • PoE (802.3af/at)
Power consumption	...	...	...	...	≤ 18 W	1.35 W (total)	...
Housing	...	...	...	...	Plastic (ABS)	Plastic (PC)	...
Operation temp	...	...	...	...	...	-25 °C ... 65 °C	...
Color	...	Black	Black	Black	Black + Silver	...	...
"Index of Protection"	...	...	...	...	—	IP20	...
Operation temp	...	...	...	...	-10 °C ... 55 °C	...	...
Weight	0.09 kg	1.1 kg	3.11 kg	2.7 kg	• 0.22 kg (without stand) • 0.24 kg (with stand)	0.03 kg (single element)	0.061 kg
Dimensions	120 x 90 x 36 mm	195 x 119 x (70 ... 250) mm	516 x 508 x 77 mm	226 x 229 x (45 ... 508) mm	• 116 x 107 x 22 mm (without stand) • 116 x 107 x 78 mm (with stand)	51 x 51 x 24 mm (single element)	79 x 64 x 23 mm
Supported languages	...	...	...	...	English	...	...
Manufacturer / Brand	DELTA	...	...	...	DAHUA	ATTE	DAHUA
Guarantee	3 years	2 years	2 years	2 years	3 years	3 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00