




	<a href="#">SWITCH POE GTX-A1-06-42 4-PORT</a>	<a href="#">SWITCH POE IP-8-20-L2 8- PORT ATTE</a>	<a href="#">FLUSH BOX 4-GANG PK-4X60/K-G/EPN Elektro- Plast</a>
			
	36.87 EUR 36.87 EUR	247.19 EUR 247.19 EUR	4.84 EUR 4.84 EUR
Number of sections	...	...	4
"Index of Protection"	...	...	—
LAN ports	<ul style="list-style-type: none"> <li>• 4 x RJ45 ( 1 x Hi-PoE + 3 x PoE (802.3af/at) ),</li> <li>• 2 x RJ45 - Uplink</li> </ul>	<ul style="list-style-type: none"> <li>• 2 x RJ45 10/100/1000 Base-TX - Uplink,</li> <li>• 8 x RJ45 10/100 Base-TX + PoE (802.3af/at) / Passive PoE</li> </ul>	...
Material	...	...	Plastic
Color	...	...	Brick red
Montage hole diameter	...	...	4 x Ø 67 mm
Management	—	—	...
LED diodes	Power, V - VLAN (Port Isolation), S - Extend, PoE, Link/Act	Power, LAN	...
Transmission speed	10 / 100 Mbps : 2 x Port LAN - Uplink + 4 x Port LAN & PoE	<ul style="list-style-type: none"> <li>• 10 / 100 Mbps : 8 LAN &amp; PoE ports,</li> <li>• 10 / 100 / 1000 Mbps : 2 LAN ports</li> </ul>	...
Operation modes	<ul style="list-style-type: none"> <li>• N - Normal - the device operates as normal PoE switch</li> <li>• V - VLAN (Port Isolation) - 1 ... 4 ports are isolated from each other and separately work with the 5, 6 ports</li> <li>• S - Extend - Range : 250 m @ 10 Mbps</li> </ul>	...	...
Maximal output power	<ul style="list-style-type: none"> <li>• 60 W / port Hi-PoE - Port 1</li> <li>• 30 W / port PoE - 2 ... 4 ports</li> </ul>	<ul style="list-style-type: none"> <li>• 40 W @ Passive PoE - 1 ... 8 ports,</li> <li>• 30 W @ PoE (802.3at) - 1 ... 8 ports,</li> <li>• 15.4 W @ PoE (802.3af) - 1 ... 8 ports</li> </ul>	...
Maximal total power	65 W	96 W	...
MAC addresses table	1k	...	...

Main features	<ul style="list-style-type: none"> <li>• MDI/MDI-X auto detection feature - auto detecting the data transmission mode</li> <li>• Full Duplex: IEEE802.3x, Half Duplex: Back Pressure</li> <li>• Auto-learning and Auto-aging functions support for MAC addresses</li> <li>• PD Alive mode - monitoring of the ports that power PoE devices and automatic restart by cutting off the power supply when an unresponsive device is detected</li> <li>• MTBF (Mean Time Between Faults) : 50000 h</li> </ul>	<ul style="list-style-type: none"> <li>• Supported PoE devices: 802.3af/at, Passive PoE</li> <li>• Possibility to connecting in cascade @ 90 W</li> <li>• Built-in switching power supply : 48 V DC / 96 W</li> <li>• Efficiency : 92 %</li> <li>• PSU thermal protection</li> <li>• Short-circuit protection</li> <li>• Overload protection</li> <li>• The ability to independently turn on and off the PoE power for each of the LAN 1 ... LAN 8 ports</li> <li>• Electronic fuse independently for each PoE channel</li> <li>• The modular design streamlines service tasks and enables quick and easy system expansion</li> <li>• The raster system of module assembly facilitates the expansion of the device by further modules</li> <li>• The ABOX-L2 mounting enclosure is equipped with 11 cable entries with glands in the 10 x M16 + 1 x M20 arrangement</li> <li>• "Index of Protection" : IP56</li> </ul>	<ul style="list-style-type: none"> <li>• Flush-mounted, for hollow walls</li> <li>• 4 special screws with holders to fastening to the wall - included</li> </ul>
Certificates	CE, FCC Class B	...	...
Protections	Overvoltage $\pm$ 3 kV	...	...
Power supply	100 ... 265 V AC	• 190 ... 260 V AC - Built-in APS-90-480-OF switching mode power supply	...
Operation temp	-10 °C ... 55 °C	...	...
Weight	0.6 kg	1.04 kg	0.088 kg
Manufacturer / Brand	...	ATTE	Elektro-Plast
Dimensions	190 x 130 x 35 mm	248 x 198 x 96 mm	4 x Ø 60 x 47 mm - Internal dimensions 282 x 72 x 48 mm - External dimensions
Guarantee	2 years	3 years	2 years