




	IP CAMERA DS-2CD6424FWD-30(2.8MM) (8M) - 1080p Hikvision	ANGULAR COMPRESSION PLUG BNC-WK/ZAC-RG59	WIRELESS PIR DETECTOR KX12DOHT-WE PYRONIX
			
	507.21 EUR 507.21 EUR	1.10 EUR 1.10 EUR	52.40 EUR 52.40 EUR
Standard	TCP/IP
Support	Wireless alarm systems PYRONIX Enforcer
Sensor	1/2.7 " Progressive Scan CMOS
Matrix size	2.1 Mpx
Battery power supply	1 x CR123A - alkaline battery (included)
Battery lifetime	~ 2 years
Frequency range	868 MHz
Connector type	...	BNC Angular plug	...
Attachment of connector elements	...	Compression mounting	...
Radio communication range (at open area)	max. 1600 m
Recommended installation height	1.8 ... 2.4 m
Impedance	...	75 Ω	...
Material	...	Brass (Nickel-plated)	...
Detection angle / Detection range	85 ° / 12 m
Application	...	Coaxial cable	...
Digital temperature compensation	✓
Dielectric diameter	...	max. 5.7 mm	...
Resolution	1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx , 1280 x 720 - 720p
Pet immunity	—
Wire mounting	...	Pressing	...
Environment class	II
Cable diameter	...	max. 8.5 mm	...
Shield fastening	...	Compression mounting	...
Watertightness	...	✓	...
Example of application	...	RG59	...
Operation temp	-10 °C ... 50 °C
Compliance with standards	EN 50131-1 EN 50131-2-2 EN 50131-5-3 EN 50130-4 EN50130-5 EN 61000-6-3

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Main features	...	<ul style="list-style-type: none"> • Wide frequency range • Very low loss in the whole operating band • Perfect matching to the transmission line within the whole operating band • Watertightness of connector with cable connection • Resistance to corrosion - made of non-ferrous metals and highest-quality dielectric • Properly compressed connection is highly resistant to break • Many patent-pending solutions • Wire : 0.55 ... 0.80 mm • To crimp use the crimping tool ZAC/MSR-2K, HT-5082R 	<ul style="list-style-type: none"> • Advanced temperature compensation • Quick pairing of the detector with the alarm control panel using a single button • Blue Wave - immunity to false alarms • Quad Sensor • Tamper protection (detection of removing from mounting surface and enclosure opening) • Test mode
Lens	2.8 mm
Manufacturer's code	KX12DQ-WE
View angle	<ul style="list-style-type: none"> • 109.4 ° (manufacturer data) • 111 ° (our tests result)
Min. illumination	0.01 Lux / F1.2
Audio	<ul style="list-style-type: none"> • External microphone input • Audio output • Bi-directional audio streaming support • Audio detection
RS-485 interface	—
RS-232 interface	✓
Bitrate	32 ... 16384 kbps - H.264
Main stream frame rate	25 fps @ 1920 x 1080
Network protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, IEEE 802.1x, QoS, IPv6, Bonjour
ONVIF	16.12
Image compression method	H.264+ / H.264 / MJPEG
Network interface	10/100 Base-T (RJ-45)
Alarm inputs / outputs	1 / 1
Mobile phones support	Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application iVMS-4500 or Hik-Connect • iOS (iPhone): Free application iVMS-4500 or Hik-Connect
Default admin user / password	admin / -
Default IP address	192.168.1.64
Web browser access ports	80
PC client access ports	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application
Mobile client access ports	8000
Port ONVIF	80

RTSP URL	<ul style="list-style-type: none"> • Main stream rtsp://192.168.1.64:554/Streaming/Channels/101/ - RTSP - without authorization rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ - with authorization • Sub stream rtsp://192.168.1.64:554/Streaming/Channels/102/ - RTSP - without authorization rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/ - with authorization
Memory card slot	Micro SD memory cards up to 128GB support (possible local recording)
Power supply	<ul style="list-style-type: none"> • 12 V DC / 540 mA, • PoE (802.3af)
Power consumption	< 6.5 W
Main features	<ul style="list-style-type: none"> • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • Lens focus loss detection • Configurable Privacy Zones • Intelligent image analysis - crossing the line (tripwire), intrusion, scene changing, face detection
Length of the cable	8 m
Operation temp	-30 °C ... 60 °C
Weight	0.26 kg - Network module 0.28 kg - Camera	0.024 kg	0.124 kg
Dimensions	105 x 78 x 26 mm - Network module Ø 26 x 57 mm - Camera	14.5 x 40 x 28 mm	117 x 69 x 50 mm
Supported languages	English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Polish, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Vietnamese, Italian
Manufacturer / Brand	Hikvision	...	PYRONIX
SAP Code	300720059	...	361300016
Guarantee	3 years	2 years	2 years