




	SWITCH POE DS-3E0310HP-E 8-PORT Hikvision	INDUSTRIAL POE SWITCH PFS3010-8GT-96-V2 8-PORT DAHUA	ADAPTER WT-55/GT-2.5
			
	139.08 EUR 139.08 EUR	116.90 EUR 116.90 EUR	0.95 EUR 0.95 EUR
Connector type	Adapter : Plug 2.1 / 5.5 mm , Socket 2.5 / 5.5 mm
Material	Metal / PET
LAN ports	<ul style="list-style-type: none"> • 2 x RJ45 10/100/1000 Base-TX - Uplink, • 8 x RJ45 10/100 Base-TX (1 x Hi-PoE (802.3af/at/bt) + 7 x PoE (802.3af/at)) 	<ul style="list-style-type: none"> • 1 x RJ45 10/100/1000 Base-TX + Hi-PoE / PoE (802.3bt), • 7 x RJ45 10/100/1000 Base-TX + PoE (802.3af/at), • 2 x RJ45 10/100/1000 Base-TX - Uplink ports 	...
Management	—	—	...
Transmission speed	10 / 100 / 1000 Mbps : 2 LAN ports 10 / 100 Mbps : 8 LAN & PoE ports	<ul style="list-style-type: none"> • 10 / 100 / 1000 Mbps - 8 LAN & PoE ports, • 10 / 100 / 1000 Mbps - 2 Uplink ports 	...
Maximal output power	...	30 W / port PoE 60 W / port Hi-PoE 90 W / port PoE 802.3bt	...
Maximal total power	110 W	96 W	...
MAC addresses table	16k	4k	...
Operation modes	<ul style="list-style-type: none"> • Extend On : 150 m, 10 Mbps @ Hi-PoE (802.3bt) / 250 m, 10 Mbps @ PoE (802.3af/at) • Extend Off : 100 m, 100 Mbps @ Hi-PoE (802.3af/at/bt) 	<ul style="list-style-type: none"> • Extend On : 250 m, 10 Mbps @ UTP cat. 5e, 6 • Extend Off : 100 m, 1000 Mbps @ UTP cat. 5e, 6 	...

Main features	...	<ul style="list-style-type: none"> • PoE power mode : The device supports 8-pin power supply • Intelligent management of Power Supply Unit power's output stage • protection against lightning discharges and voltage differences and strokes between devices • PoE Watchdog / PD Alive mode - monitoring of the ports that power PoE devices and automatic restart by cutting off the power supply when an unresponsive device is detected • Kensington Lock 	<ul style="list-style-type: none"> • Very easy and quick assembly • Corrosion resistance
LED diodes	Power, PoE Max, PoE, Link/Act	Power, Link/Act, PoE	...
Certificates	CE	CE	...
Power supply	48 V DC / 2.5 A (power adapter included)	48 ... 57 V DC / 1.81 A (power adapter included)	...
SAP Code	301801346
Operation temp	...	-10 °C ... 55 °C	...
Weight	0.57 kg	0.52 kg	0.008 kg
Dimensions	218 x 107 x 28 mm	190 x 100 x 30 mm	Ø 12 x 36 mm
Manufacturer / Brand	Hikvision	DAHUA	...
Guarantee	3 years	5 years	2 years