




	HANDLE FOR REMOTE CONTROL MC-755 MACLEAN	AHD, HD-CVI, HD-TVI, PAL CAMERA BCS-DMQ2803IR3-B - 8.3 Mpx 4K UHD 3.6 mm	EXTENDER HDMI+USB-EX-100-4K
			
	5.94 EUR 5.94 EUR	106.90 EUR 106.90 EUR	202.41 EUR 202.41 EUR
Max. width of the remote control	47 mm
Material	ABS
Standard	...	AHD / HD-CVI / HD-TVI / CVBS	...
Sensor	...	1/1.8 " Progressive Scan CMOS	...
Matrix size	...	8.3 Mpx	...
Supported HDMI resolutions	480p, 576i, 576p, 720p, 1080i, 1080p, 4K x 2K, 4K UHD
Resolution	...	3840 x 2160 - 8.3 Mpx 4K UHD, 960 x 576 - 960H, PAL	...
Range of IR illumination	...	30 m	...
IR illuminator power adjustment	...	Automatic	...
Maximal transmission range	<ul style="list-style-type: none"> • 70 m UTP cat. 6 @ 4K UHD, • 70 m UTP cat. 5, 5e @ 1080p • 50 m UTP cat. 5e @ 4K UHD (our tests result)
Lens	...	3.6 mm, F1.2	...
View angle	...	<ul style="list-style-type: none"> • 105 ° (manufacturer data) • 85 ° (our tests result) 	...
S/N ratio	...	35 dB	...
Main features	<ul style="list-style-type: none"> • Built-in basis magnets allow mounting to metal surfaces • Aesthetic and solid construction • Very easy and quick assembly 	...	<ul style="list-style-type: none"> • Very good image quality with no visible distortions caused by compression • No delays in video transmission • No delays in mouse control operations • Transition of the HDMI signal in the transmitter • S/PDIF output
Video output	...	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω	...
OSD menu	...	✓	...

Operation temp	-20 °C ... 60 °C
Permissible relative humidity	0 % ... 90 % (non-condensing)
Main features	...	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • 2D-DNR, 3D-DNR - Digital Noise Reduction • BLC - configurable Back Light Compensation • Anti-Flicker - The technology eliminates the tiring eyes flickering image effect • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Auto White Balance • Mirror - Mirror image 	<ul style="list-style-type: none"> • Extender also allows to extend an USB 2.0 port, eg. in order to control the recorder using the mouse
Power supply	...	12 V DC / 830 mA	<ul style="list-style-type: none"> • Transmitter 5 V DC / 2 A (power adapter included) • Receiver 5 V / 2 A (power adapter included)
Power consumption	...	< 10 W	...
Housing	...	Dome, Metal	...
Color	Black	White	...
"Index of Protection"	...	IP66	...
Vandal-proof	...	—	...
Operation temp	...	-20 °C ... 60 °C	...
Weight	0.03 kg	0.28 kg	0.29 kg
Dimensions	110 x 55 x 27 mm	Ø 94 x 80 mm	150 x 107 x 28 mm - Transmitter or receiver dimensions
Manufacturer / Brand	MACLEAN	BCS	...
Guarantee	2 years	3 years	2 years