

| | FLUSH BOX PK-60F/K-G/SG/EPN Elektro-Plast | FLUSH BOX S-60GFW SIMET | SMART PROXIMITY SWITCH PROXISWITCH-V2/BLEBOX 12 ... 24 V DC |
|-------------------------|---|--|--|
| |  |  |  |
| | 1.07 EUR 1.07 EUR | 0.51 EUR 0.51 EUR | 12.09 EUR 12.09 EUR |
| Application | ... | ... | Non-contact switching on and off |
| Number of sections | 1 | 1 | ... |
| Rated voltage | ... | ... | 12 ... 24 V DC |
| Maximal total load | ... | ... | 120 W |
| Total maximal current | ... | ... | 5 A |
| Number of inputs | ... | ... | 0 |
| Number of outputs | ... | ... | 1 |
| Connector type | ... | ... | screw terminals |
| Wireless | ... | ... | — |
| Mobile phones support | ... | ... | — |
| Material | halogen free and inflammable | Plastic | ... |
| Mounting holes distance | ... | 60 mm | ... |
| Montage hole diameter | Ø 68 mm | ... | ... |
| Main features | <ul style="list-style-type: none"> • Flush-mounted, deep, for hollow walls • 850 °C flammability index • 2 special screws with holders to fastening to the wall - included | <ul style="list-style-type: none"> • Flush-mounted, serial, deep • 4 fixing points • 2 Mounting screws - included | <ul style="list-style-type: none"> • Operation modes : bistable, bistable + state memory, monostable NO, monostable NC, • Detection range : 3 cm • Trigger time : max. 8 s • Possibility to hide the sensor • Automatic calibration • LED indication |
| Housing | ... | ... | Plastic |
| "Index of Protection" | — | IP20 | IP20 |
| Color | Yellow | Orange | Black |
| Operation temp | ... | ... | -20 °C ... 50 °C |
| Weight | 0.026 kg | 0.024 kg | 0.018 kg |
| Dimensions | Ø 60 x 61 mm - Internal dimensions Ø 71 x 62 mm - External dimensions | 84 x 65 x 80 mm | 39 x 39 x 16 mm |
| Manufacturer / Brand | Elektro-Plast | SIMET | BleBox |
| Guarantee | 2 years | 2 years | 2 years |