



	ACCESS POINT 4G LTE +ROUTER RUT200 2.4 GHz 300 Mbps Teltonika	IP CAMERA IPC2124LE-ADF28KMC-WL ColorHunter - 4 Mpx 2.8 mm UNIVIEW
		
	153.23 CAD 153.23 CAD	255.56 CAD 255.56 CAD
Standard	...	TCP/IP
Frequency range	2.4 GHz	...
Sensor	...	1/3 " Progressive Scan CMOS
Matrix size	...	4 Mpx
Antenna type	1 x Omnidirectional antenna Wi-Fi - 5 dBi (SMA connector) , 2 x Omnidirectional antenna 4G LTE - 4 dBi (SMA-RP connector)	...
Standards	IEEE 802.11 b/g/n, 4G LTE, 3G, 2G	...
Resolution	...	2688 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p
Lens	...	2.8 mm
View angle	...	• 113 ° (manufacturer data) • 97 ° (our tests result)
Range of IR illumination	...	30 m
Baud rates	11n : 300 Mbps 11g : 54 Mbps 11b : 11 Mbps LTE : 150 / 42 / 0.234 Mbps (4G / 3G / 2G)	...
White light LED illuminator range	...	30 m
S/N ratio	...	> 52 dB
RS-485 interface	...	—
Memory card slot	...	Micro SD memory cards up to 128GB support (possible local recording)
LAN ports	• 1 x 10/100 Mbps - WAN • 1 x 10/100 Mbps - LAN	...
Image compression method	...	Ultra 265 / H.265 / H.264 / MJPEG
Alarm inputs / outputs	...	—
Audio	...	• Microphone built-in • Speaker built-in • Audio detection • Bi-directional audio streaming support

Main stream frame rate	...	25 fps @ 4 Mpx
Transmitter power	≤ 20 dBm @ 2.4 GHz ≤ 23 dBm @ 4G LTE ≤ 24 dBm @ 3G WCDMA ≤ 33 dBm @ 2G GSM	...
Network interface	...	10/100 Base-T (RJ-45)
LED indicators	Power, WAN, WLAN, LAN, LTE (4G / 3G / 2G), Signal indicator	...
Network type	4G, 3G, 2G	...
Network protocols	...	IPv4/IPv6, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, IEEE 802.1x, SNMP, SSL / TLS
WEB Server	...	Built-in
LTE	✓	...
Max. number of on-line users	...	32
QSS	—	...
ONVIF	...	✓
WDS	—	...
DHCP server	✓	...
Mobile phones support	...	Access by a cloud (P2P) • Android: Free application EZView • iOS (iPhone): Free application EZView
Default IP address	...	DHCP or 192.168.1.13
Default admin user / password	...	admin / 123456
Web browser access ports	...	80, 554
PC client access ports	...	Port no.: 80 or access by a cloud (P2P) - PC: Free application EZStation
Mobile client access ports	...	80
Protections	<ul style="list-style-type: none"> • WPA2-Enterprise - PEAP • WPA-PSK/WPA2-PSK • WPA-EAP • AES-CCMP • WEP • TKIP • Auto Cipher modes • Client separation • SSID hiding • MAC addresses filtering 	...
Port ONVIF	...	80
Management interface	Web browser, Teltonika RMS application, SMS	...

RTSP URL	...	rtsp://192.168.1.13:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.13:554/unicast/c1/s1/live - Sub stream
Main features	<ul style="list-style-type: none"> • SIM socket • DHCP Relay support • DHCP client list • Static / dynamic routing • VPN support • Default address : 192.168.1.1 • Configuration using the Teltonika RMS application • WAN Connection Backup - thanks to the fully functional WAN / LAN port, you can use various types of backup connections, including cable, fiber and DSL modems 	...
Operation temp	-40 °C ... 75 °C	...
Main features	...	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 2D-DNR, 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • ROI - improve the quality of selected parts of image • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • NAS - Network Attached Storage support • Corridor mode - useful for monitoring corridors, entrance gates and narrow rooms • BLC/HLC - Back Light / High Light Compensation • Possibility to change the resolution, quality and bit rate • Mirror - Mirror image • Privacy zones - max. 4 • Motion detection with human/vehicle silhouette recognition • Sharpness - sharper image outlines • Intelligent image analysis : intrusion, crossing the line (tripwire) (human silhouette)
Permissible relative humidity	10 % ... 90 % (non-condensing)	...

Power supply	<ul style="list-style-type: none"> • 9 V DC / 1 A (power adapter included) • 9 ... 30 V DC • 9 ... 30 V DC - Passive PoE, Powering from LAN1 	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 750 mA
Power consumption	≤ 6.5 W	≤ 9 W
Housing	...	Compact, Metal + Plastic
Color	...	White
"Index of Protection"	...	IP67
Vandal-proof	...	—
Operation temp	...	-30 °C ... 60 °C
Weight	0.13 kg	0.41 kg
Dimensions	83 x 80 x 25 mm	191 75 x 74 mm
Supported languages	...	Polish, English, Czech, Spanish, Dutch, French, German, Portuguese, Slovak, Hungarian, Italian
Manufacturer / Brand	Teltonika	UNIVIEW
Guarantee	2 years	3 years