



	AHD, HD-CVI, HD-TVI, CVBS, TCP/IP DVR APTI-XB0401H-S32 4 CHANNELS	IP CAMERA DS-2CD2T43G0-I8(2.8MM) - 4.0 Mpx Hikvision
		
	57.46 EUR 57.46 EUR	242.00 EUR 242.00 EUR
Sensor	...	1/3 " Progressive Scan CMOS
Scanning system	...	Progressive
Matrix size	...	4.1 Mpx
Standard	AHD, HD-CVI, HD-TVI, PAL, TCP/IP	TCP/IP
Video inputs	4 pcs BNC - AHD / HD-CVI / HD-TVI / CVBS	...
Video outputs	<ul style="list-style-type: none"> • 1 pcs HDMI • 1 pcs VGA • 1 pcs Composite Video (CVBS) - BNC socket 	...
Audio inputs	2 pcs CINCH	...
Audio outputs	1 pcs CINCH	...
Resolution	...	2688 x 1520 - 4.0 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p 1280 x 720 - 720p
Image compression method	H.265+ / H.265 / H.264+ / H.264	...
Lens	...	2.8 mm
View angle	...	<ul style="list-style-type: none"> • 103 ° (manufacturer data) • 100 ° (our tests result)
Compression	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Range of IR illumination	...	80 m
Audio	...	—
Memory card slot	...	Micro SD memory cards up to 128GB support (possible local recording)
Bitrate	...	32 ... 16384 kbps
Main stream frame rate	...	25 fps @ 4.0 Mpx
Network interface	...	10/100 Base-T (RJ-45)

Image records resolutions	<ul style="list-style-type: none"> • AHD / HD-TVI : 8M-N - 1920 x 2160 px, 5 Mpx - 2592 x 1944 px, 5M-N - 1296 x 1944 px, 4 Mpx - 2560 x 1440 px, 4M-N - 1280 x 1440 px, 3 Mpx - 2048 x 1536 px, 1080p - 1920 x 1080 px, 720p - 1280 x 720 px, • HD-CVI : 8M-N - 1920 x 2160 px, 4 Mpx - 2560 x 1440 px, 4M-N - 1280 x 1440 px, 1080p - 1920 x 1080 px, 720p - 1280 x 720 px, • CVBS : 960H - 960 x 576 px, • IP : max. 5 Mpx - 2592 x 1944 px 	...
Network protocols	...	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, IEEE 802.1x, QoS, IPv6, Bonjour
WEB Server	...	Built-in, NVR compliance
Max. number of on-line users	...	6
ONVIF	...	16.12
Recording speed adjustment	<ul style="list-style-type: none"> 5 Mpx IP @ 1 ... 25 fps 8M-N @ 1 ... 8 fps 5 Mpx @ 1 ... 6 fps 5M-N @ 1 ... 10 fps 4 Mpx @ 1 ... 8 fps 4M-N @ 1 ... 15 fps 3 Mpx @ 1 ... 9 fps 1080p @ 1 ... 15 fps 720p @ 1 ... 25 fps 960H @ 1 ... 25 fps for each channel 	...
Port ONVIF	...	80



Operation modes	<ul style="list-style-type: none"> • 4 x AHD / HD-CVI / HD-TVI / CVBS + 2 x IP max. 5 Mpx • 2 x AHD / HD-CVI / HD-TVI / CVBS + 7 x IP max. 5 Mpx • 16 x IP max. 5 Mpx <p>All modes allow for any combination of the AHD, HD-CVI, HD-TVI, CVBS cameras</p>	...
RTSP URL	...	<ul style="list-style-type: none"> • Main stream rtsp://192.168.1.64:554/Streaming/Channels/101/ - RTSP - without authorization rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ - with authorization • Sub stream rtsp://192.168.1.64:554/Streaming/Channels/102/ - RTSP - without authorization rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/ - with authorization
Recording modes	Motion Detection, Schedule	...
RS-485 interface	...	—
Supported hard drives	1 x 8 TB SATA	...
External storage devices backup	Records backup at (.avi) format to USB (pendrive)	...
Searching and playback the records	Records searching: timeline or file list. Playback: forward, backward, fast, slow. Records playback from max. 4 channels in the same time	...
Network functions	<ul style="list-style-type: none"> • Network Client Software (iVMS320): live view, playback and backup of the records • IE browser: live view, playback and backup of the records and configuration of the recorder parameters 	...
Mobile phones support	<p>Port no.: 6000 or access by a cloud (P2P)</p> <ul style="list-style-type: none"> • Android: Free application BitVision, Android: Free application iVMS320 • iOS (iPhone): Free application BitVision, iOS: Free application iVMS320 	<p>Port no.: 8000 or access by a cloud (P2P)</p> <ul style="list-style-type: none"> • Android: Free application iVMS-4500 or Hik-Connect • iOS (iPhone): Free application iVMS-4500 or Hik-Connect



Default IP address	192.168.1.88	192.168.1.64
Default admin user / password	admin / 12345	admin / - The administrator password should be set at the first start
Web browser access ports	80, 5000, 554	80
PC client access ports	80, 5000, 554	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application
Main features	...	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners • Anti-Flicker - The technology eliminates the tiring eyes flickering image effect • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • Possibility to change the resolution, quality and bit rate • Motion Detection • Configurable Privacy Zones • Mirror - Mirror image • Intelligent image analysis : intrusion, crossing the line (tripwire), face detection
Mobile client access ports	80, 5000, 6000	8000
Alarm inputs / outputs	4 / 1	—
PTZ control	Pelco-D, Pelco-P	...
Motion Detection	Split the screen into zones : 22 x 18 motion zones	...
USB	2 pcs USB 2.0	...
Mouse support	✓	...
Power consumption	...	≤ 11.5 W @ 12 V DC ≤ 12.5 W @ PoE
IR remote controller in the set	—	...
Housing	...	Compact, Metal
Power supply	12 V DC / 2 A (power adapter included)	• PoE (802.3af), • 12 V DC / 950 mA
"Index of Protection"	...	IP67
Color	Black	White
Operation temp	...	-30 °C ... 60 °C
Country of origin	China	...

Supported languages	Polish, English, Bulgarian, Czech, French, Greek, Spanish, Dutch, German, Portuguese, Russian, Romanian, Turkish, Hungarian, Italian	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Vietnamese, Italian
Weight	0.73 kg	1.1 kg
Dimensions	260 x 226 x 45 mm	Ø 105 x 300 mm
Manufacturer / Brand	APTI	Hikvision
SAP Code	...	311300861
Guarantee	2 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00