




	RFID PROXIMITY CARD ATLO-307S*P200 13.56 MHz S50	IP CAMERA IPC-HDW1239DT-PV-STW Wi-Fi, Smart Dual Light Active Deterrence - 1080p 2.8 mm DAHUA	FLUSH BOX S-60KFW SIMET
			
	200.00 PLN 200.00 PLN	169.00 PLN 169.00 PLN	1.28 PLN 1.28 PLN
Standard	...	IP	...
Number of sections	1
In package	200 pcs The price for package
Standard	13.56 MHz S50
Compatibility	ISO/IEC 14443A
Possibility of programming the serial number (ID)	—
Ability to write to internal memory	1 kB
Serial Number overprint	—
Resolution	...	1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx , 1280 x 720 - 720p	...
Sensor	...	1/3 " Progressive Scan CMOS	...
Lens	...	2.8 mm	...
Material	Plastic
View angle	...	98 °	...
Main features	Range : ~ 10 cm ,	...	<ul style="list-style-type: none"> • Flush-mounted, serial, shallow • flammability index : 650 °C • 4 fixing points • 2 Mounting screws - included
Mounting holes distance	60 mm
Range of IR illumination	...	30 m	...
White light LED illuminator range	...	30 m	...
S/N ratio	...	> 56 dB	...
Memory card slot	...	Micro SD card support up to 256GB	...
Image compression method	...	H.265+ / H.265 / H.264+ / H.264	...
Alarm inputs / outputs	...	—	...
Audio	...	<ul style="list-style-type: none"> • Microphone built-in, • Speaker built-in, • Bi-directional audio streaming support • Audio output • Audio detection 	...
Main stream frame rate	...	25 fps @ 1080p	...
Network interface	...	<ul style="list-style-type: none"> • Wi-Fi - IEEE 802.11 b/g/n, 2.4 GHz, • 10/100 Base-T (RJ-45) 	...
WEB Server	...	Built-in	...
Max. number of on-line users	...	20	...
ONVIF	...	✓	...
Mobile phones support	...	Port no.: 37777 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application DMSS • iOS (iPhone): Free application DMSS 	...
Default IP address	...	192.168.1.108	...
Default admin user / password	...	admin / - The administrator password should be set at the first start	...
Web browser access ports	...	80, 37777	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

PC client access ports	...	37777	...
Mobile client access ports	...	37777	...
Port ONVIF	...	80	...
RTSP URL	...	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream	...
Main features	...	<ul style="list-style-type: none"> • Active deterrence function • D-WDR - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • BLC/HLC - Back Light / High Light Compensation • Possibility to change the resolution, quality and bit rate • Image rotation and mirror • Motion Detection - max. 4 configurable zones - Human detection • Privacy zones - max. 4 	...
Power supply	...	12 V DC / 580 mA (power adapter included)	...
Power consumption	...	≤ 6.9 W @ 12 V DC	...
Housing	...	Dome - Plastic	...
Color	...	White	Orange
"Index of Protection"	...	IP67	IP20
Vandal-proof	...	—	...
Operation temp	...	-40 °C ... 60 °C	...
Weight	0.006 kg	0.32 kg	0.015 kg
Dimensions	86 x 54 x 0.8 mm	Ø 110 x 102 mm	84 x 65 x 42 mm
Supported languages	...	English, Spanish, Russian	...
Manufacturer / Brand	ATLO	DAHUA	SIMET
Guarantee	2 years	3 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00