



	SWITCH POE APTI-POE0402-60W-V2 4-PORT	AHD, HD-CVI, HD-TVI, CVBS, TCP/IP DVR IDS-7204HTHI-M1/S(C)/4A+4/1ALM 4 CHANNELS ACUSENSE Hikvision
		
	34.41 EUR 34.41 EUR	372.96 EUR 372.96 EUR
LAN ports	6 x RJ45 (4 x IEEE 802.3af)	...
Management	—	...
Standard	...	AHD, HD-CVI, HD-TVI, CVBS, TCP/IP
LED diodes	LAN, WAN, PoE	...
Video inputs	...	4 pcs BNC - AHD / HD-CVI / HD-TVI / CVBS
Transmission speed	<ul style="list-style-type: none"> • 10 / 100 Mbps : 2 x Uplink, • 10 / 100 Mbps : 4 x LAN & PoE ports 	...
Maximal output power	30 W / port PoE	...
Video outputs	...	<ul style="list-style-type: none"> • 1 pcs HDMI 4K • 1 pcs VGA • 1 pcs CVBS - BNC socket There is a possibility to configure a SPOT function on one of the output
Maximal total power	60 W	...
MAC addresses table	1k	...
Audio inputs	...	<ul style="list-style-type: none"> • 4 pcs CINCH, • 4 pcs Coaxial audio - Audio from cameras
Audio outputs	...	1 pcs CINCH
Main features	<ul style="list-style-type: none"> • 2 x Port Uplink • Range PoE : 250 m - The EXTEND mode enabled • Mounts for mounting the device in the RACK 10" system 	...
Certificates	CE	...
Image compression method	...	H.265+ / H.265 / H.264+ / H.264
Operation temp	-10 °C ... 55 °C	...



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Image records resolutions	...	<ul style="list-style-type: none"> • HD-TVI / HD-CVI : 8.3 Mpx 4K UHD - 3840 x 2160 , • HD-TVI : 5 Mpx (3K) - 2960 x 1665 , 3 Mpx - 1920 x 1536 , • HD-TVI / AHD / HD-CVI : 5 Mpx - 2560 x 1944 , 3.7 Mpx - 2560 x 1440 , 1080p - 1920 x 1080 , 720p - 1280 x 720 , • CVBS : 960H - 960 x 576 , D1 - 704 x 576 , • IP : max. 8.3 Mpx - 3840 x 2160
Recording speed adjustment	...	8.3 Mpx IP @ 1 ... 25 fps 8.3 Mpx @ 1 ... 15 fps 5 Mpx @ 1 ... 20 fps 3.7 Mpx @ 1 ... 25 fps 3 Mpx @ 1 ... 18 fps 1080p @ 1 ... 25 fps 720p @ 1 ... 25 fps 960H @ 1 ... 25 fps D1 @ 1 ... 25 fps for each channel
Operation modes	...	4 x HD-TVI / AHD / HD-CVI / PAL / IP + 4 x IP
Recording modes	...	Manual, Sensor, Motion detection, Schedule
Supported hard drives	...	1 x 10 TB SATA
External storage devices backup	...	Backup to USB drive (pendrive, external drive)
Searching and playback the records	...	Records searching: timeline or file list. Playback: forward, fast, slow. Playback max. 4 cameras in the same time
Network interface	...	1 x RJ-45 - 10/100/1000 Base-T
Bitrate	...	32 ... 16384 kbps
Network functions	...	Network Client Software and IE browser: live view, playback and backup of the records, partial configuration of the recorder parameters
Network protocols	...	TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP, HTTPS, ONVIF
Mobile phones support	...	Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application iVMS-4500 or Hik-Connect • iOS (iPhone): Free application iVMS-4500 or Hik-Connect
Default IP address	...	DHCP or 192.168.1.64
Default admin user / password	...	admin / -
Web browser access ports	...	80
PC client access ports	...	554 RTSP, 8000



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Mobile client access ports	...	8000
Port ONVIF	...	80
RTSP URL	...	<ul style="list-style-type: none"> • rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no01/ - Main stream • rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no02/ - Sub stream
Alarm inputs / outputs	...	4 / 1
PTZ control	...	RS-485 PELCO-D/P Control compatible with coax HD-TVI Hikvision
Motion Detection	...	2.0
Main features	...	<ul style="list-style-type: none"> • DVR from the AcuSense series, • Intelligent image analysis : crossing the line (tripwire), intrusion, Deep Learning technology • Smart motion detection (with recognizing people and vehicles) • Filtering of false alarms based on the recognition of persons and vehicles
USB	...	<ul style="list-style-type: none"> • 1 pcs USB 2.0 • 1 pcs USB 3.0
Mouse support	...	✓
IR remote controller in the set	...	—
Power supply	230 V AC	12 V DC / 2 A (power adapter included)
Color	...	Black
Weight	0.65 kg	1.23 kg
Dimensions	200 x 118 x 44 mm	315 x 248 x 45 mm
Supported languages	...	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Greek, Spanish, Dutch, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Italian
Manufacturer / Brand	APTI	Hikvision
SAP Code	...	300227790
Guarantee	2 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00