





	VIDEO DOORPHONE S1202A VIDOS	INDOOR PANEL M1022W-2 VIDOS	AHD, HD-CVI, HD-TVI, PAL VANDALPROOF CAMERA HAC-HDBW1200EA-0280B-S6 - 1080p 2.8 mm DAHUA	WEATHER STATION UT-A12T UNI-T
				
	168.73 EUR 168.73 EUR	110.88 EUR 110.88 EUR	69.90 EUR 69.90 EUR	14.17 EUR 14.17 EUR
Compatibility	VIDOS DUO	VIDOS DUO
Measurement	Temperature / relative humidity
Shield	...	4.3 " TFT-LCD color matrix
Standard	AHD / HD-CVI / HD-TVI / PAL	...
Sensor	1/2.7 " Fish Eye CMOS, 2 Mpx	...	" Progressive Scan CMOS	...
Measurement range	-10 °C ... 50 °C ± 1 °C
IR illuminator	—
LED illuminator	✓
Matrix size	2.0 Mpx	...
Measurement of humidity	20 % ... 95 % ± 5 %
proximity reader built-in	Standard : Unique EM 125kHz
The number of subscribers served	2
Resolution	...	480 x 272	1920 x 1080 - 1080p 1280 x 720 - 720p 960 x 576 - 960H, PAL	...
Range of IR illumination	40 m	...
IR illuminator power adjustment	Automatic	...
Lens	2.8 mm, F2.0	...
View angle	170 °	...	102 °	...
IR illuminator support	ICR - Movable InfraRed filter	...
S/N ratio	> 65 dB	...
Permissible relative humidity	max. 90 % (non-condensing)
Video output	compatible with the VIDOS DUO digital video doorphone system	...	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω	...

Main features	<ul style="list-style-type: none"> • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • DNR - Digital Noise Reduction • D-WDR - Wide Dynamic Range • BLC - configurable Back Light Compensation • HLC - High Light Compensation (spot) • Mirror - Mirror image • Auto White Balance • Privacy zones 	...
Main features	<ul style="list-style-type: none"> • Wiring - 2 wires without polarity • Relay output : 1 pcs or 2 pcs - B5 Module • Support up to 13 indoor devices (monitors / uniphones) • PIR detectors support • Permanent or cyclical zoom-up of the observed image • Electric strikes and electromagnetic locks support • Electric lock supply: 12V DC / max. 300mA • Easy to add and delete users via MASTER key fobs 	<ul style="list-style-type: none"> • Wiring - 2 wires without polarity, • Plug & Play, • Ultra-flat hands-free monitor, with speakerphone, • Backlit, touch control panel, • Microphone built-in, • Speakers built-in, • Bidirectional communication, • Possibility to extend the system with any 3 additional indoor panels or uniphones from the VIDOS DUO brand • "Do not disturb" mode - muting the device for the time set by the user, • Number of ring-tones : 12 • Support up to 4 door stations - M-SM4 Module, • Preview image from the door station with the possibility of turning on the sound and opening the gate, • Control of the electric strike and automatic gate, • Addressable internal and external intercom, • Intercom and call forwarding function, • Support up to 4 additional CCTV cameras - view from cameras possible via an additional M-K4 module, • Lighting control via an additional B5 module, • OSD menu 	...	<ul style="list-style-type: none"> • LCD display • Digital sensor • External temperature measuring probe : Length of the cable 2 m • Alarm function • Selectable measurement unit: °C / °F • Wall mounting • Integrated stand
OSD menu	OSD menu available via recorder	...
Power supply	24 V DC	20 V DC ... 28 V DC	12 V DC / 230 mA	1 x battery LR3 (AAA) (included)
Power consumption	<ul style="list-style-type: none"> ≤ 3 W (operation) ≤ 0.8 W (Standby mode) 	<ul style="list-style-type: none"> • 0.17 W (Standby mode) • 4.7 W (operation) 	≤ 2.8 W	...

Housing	Acid-proof steel / Plastic, Waterproof	Plastic	Dome, Metal	...
Color	Silver	White	White	White
"Index of Protection"	IP54	...	IP67	...
Operation temp	-20 °C ... 55 °C	0 °C ... 40 °C	...	-10 °C ... 50 °C
Vandal-proof	IK10	...
Operation temp	-40 °C ... 60 °C	...
Weight	0.79 kg	0.27 kg	0.44 kg	0.106 kg
Dimensions	220 x 119 x 52 mm	138 x 138 x 21 mm	Ø 112 x 81 mm	Ø 130 x 78 mm x 22 mm
Supported languages	...	Polish, English, French, Spanish, German, Russian, Italian	Polish, English, Chinese, French, Spanish, Japanese, Korean, German, Portuguese, Russian, Italian	...
Manufacturer / Brand	VIDOS	VIDOS	DAHUA	UNI-T
Guarantee	3 years	3 years	3 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00