

	DIAL SMART SWITCH SWITCHBOX/DOUBLEBOX W: FL 230 V AC	POWER DISTRIBUTION UNIT AK-SP-05U/G OUTLETS + 2 USB/ AKYGA	KRONE BACK MOUNT FRAME LSA-CN-10/3	OVERVOLTAGE LIMITER LE-412253 THREE-PHASE 1+2 TYPE LEGRAND	TURNBUCKLE VANT-8/PL	STRAIGHT PLUG LE-50309 230 V 2.5 A LEGRAND	CLEANER FOR RECOVERY OF POTENTIOMETERS KONTAKT-PR400 SPRAY 400 ml AG TERMOPASTY	STRAIGHT PLUG LE-50444 230 V 16 A LEGRAND
								
	153.67 PLN 153.67 PLN	59.32 PLN 59.32 PLN	7.80 PLN 7.80 PLN	905.81 PLN 905.81 PLN	11.18 PLN 11.18 PLN	10.01 PLN 10.01 PLN	26.93 PLN 26.93 PLN	72.09 PLN 72.09 PLN
Number of mounted profile modules	3 pcs
Material	Metal
Type of mounted profile modules	10PAR
Package	Spray 400 ml	...
Application	switching devices on/off	Steel lines	...	Cleaning and regeneration of potentiometers	...
Maximal current load	2.5 A	...	16 A
Device type	Overvoltage limiter, Three-phase
Grounding	---	...	✓
Electrical cable	max. 2 x 0.75 mm ²	...	max. 3 x 2.5 mm ²
Rated voltage	230 V AC	230 V AC / 50 Hz	...	230 / 400 V AC, 50 / 60 Hz	...	230 V / 50 Hz	...	230 V / 50 Hz
Maximal total load	2 x 1150 W / 1150 VA	2500 W
Response time	...	< 25 ns
Cable terminals	screw terminals	...	automatic spring terminals
Maximal voltage	320 V AC, 50 / 60 Hz
Total maximal current	2 x 5 A	10 A
Number of inputs	2
Number of outlets	...	• 5 grounded outlets 10A/250V, • 2 USB ports 2A/5V
Plug type	CEE 7/16, C type	...	CEE 7/6
Mechanical strength	IK08
Number of outputs	2
Class	1+2 type (Class B+C)
Connector type	screw terminals
Automatic delayed fuse	...	10 A / 250 V
Nominal voltage of surge suppressor	...	250 V / 50 Hz
Wireless	Wi-Fi, 2.4 GHz - IEEE 802.11g
Protection level Up L/PE, N/PE	1.2 kV @ 10/350 µs (T1) 1.7 kV @ 8/20 µs (T2)
DC filter to eliminate interferences	...	RFI ≤ 10 dB
Mobile phones support	• The wBox free application on Android • The wBox free application on iOS
Maximum stroke current	...	4.5 kA
Maximum energy absorption	...	150 J
Switch	...	with light indication
Nominal discharge current (L/PE, N/PE)	8 kA @ 10/350 µs (T1) 20 kA @ 8/20 µs (T2)
Length of the cable	...	1.5 m
Maximum stroke current (L/N, L/PE, N/PE)	50 kA @ 8/20 µs (T2)
Operation state indication	✓
Connectors type	screw terminals
Width in 17.5 mm modules	4
Main features	• Local control by physical button, • schedule, • timer, • remote access, • voice control, • The ability to set the default status of the device after a power failure, • µWiFi technology support	• Screw diameter 8 mm • Work load 140 kg • Corrosion resistance	...	Spray preparation with a brush for easy application in hard-to-reach places	...
Housing	Plastic	Plastic (ABS)	...	Plastic, DIN, TS-35 rail mounting
"Index of Protection"	IP20	IP55
Color	Black	Black	Black	...	Black
Operation temp	-20 °C ... 50 °C	5 °C ... 50 °C
Weight	0.04 kg	0.318 kg	...	0.552 kg	0.105 kg	0.015 kg	0.36 kg	0.058 kg
Dimensions	41 x 39 x 23 mm	305 x 50 x 40 mm	67 x 112 x 50 mm	71 x 83 x 70 mm	170 x 21 x 12 mm	67 x 36 x 14 mm	Ø 66 x 187 mm	122 x 43 x 42 mm
Manufacturer / Brand	BleBox	AKYGA	...	LEGRAND	...	LEGRAND	AG TERMOPASTY	LEGRAND
Guarantee	2 years	2 years	2 years	2 years	2 years	2 years	...	2 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00