





	<a href="#">RFID PROXIMITY CARD ATLO-114*P100</a>	<a href="#">WIRELESS PIR DETECTOR ATLO-AC-AP818</a>	<a href="#">SET OF UTP / 2-WIRE CONVERTERS FOR LAN+POE TRANSMISSION ETH10-2WIRE-SET 2 PCS SET ATE</a>	<a href="#">AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-T2A21-0280B - 1080p 2.8 mm DAHUA</a>
				
	44.90 EUR 44.90 EUR	8.80 EUR 8.80 EUR	88.61 EUR 88.61 EUR	54.51 EUR 54.51 EUR
Support	...	alarm control panel ATLO-AZ-WG13A-TUYA	...	...
Battery power supply	...	1 x 9V, type 6LR61 battery (included)	...	...
In package	<b>100 pcs The price for package</b>	...	...	...
Standard	...	...	...	HD-CVI, HD-TVI, AHD, PAL
Standard	Unique EM 125kHz	...	...	...
Frequency range	...	433 MHz	...	...
Sensor	...	...	...	1/2.7 " Progressive Scan CMOS
Compatibility	EM4100/4102	...	...	...
Radio communication range (at open area)	...	≤ 100 m	...	...
Possibility of programming the serial number (ID)	—	...	...	...
Recommended installation height	...	2 m	...	...
Matrix size	...	...	...	2.1 Mpx
Connectors	...	...	<ul style="list-style-type: none"> <li>• 1 pcs RJ45</li> <li>• 1 pcs terminals (screw terminals) - 0.32 ... 3.3 mm<sup>2</sup> ( 22 ... 12 AWG )</li> </ul>	...
Ability to write to internal memory	—	...	...	...
Serial Number overprint	—	...	...	...
Detection angle / Detection range	...	110 ° / 12 m	...	...
LAN ports	...	...	1 pcs RJ45 10 Mbps	...
Current consumption	...	≤ 40 μA - Standby ≤ 15 mA - Alarm signaling	...	...
Pet immunity	...	—	...	...
Resolution	...	...	...	1920 x 1080 - 1080p , 1280 x 720 - 720p , 960 x 576 - 960H, PAL
Range of IR illumination	...	...	...	20 m
Permissible relative humidity	...	≤ 85 %	...	...
IR illuminator power adjustment	...	...	...	Automatic
Lens	...	...	...	2.8 mm

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

View angle	...	...	...	<ul style="list-style-type: none"> <li>• 103 ° (manufacturer data)</li> <li>• 100 ° (our tests result)</li> </ul>
S/N ratio	...	...	...	> 65 dB
Video output	...	...	...	HD-CVI / HD-TVI / AHD / PAL, 1 Vpp / 75 Ω
Audio	...	...	...	—
Connectors description	...	...	<p>ETH10-2WIRE-TX :</p> <ul style="list-style-type: none"> <li>• PoE IN - Passive PoE ≤ 30 W, PoE (802.3at) ≤ 30 W, PoE (802.3af) ≤ 15 W ("+"-": 1, 2 pins; "+/-": 3, 6 pins) or ("+"-": 4, 5 pins; "+/-": 7, 8 pins)</li> <li>• Power</li> <li>• DATA - 2-wire</li> </ul> <p>ETH10-2WIRE-RX :</p> <ul style="list-style-type: none"> <li>• PoE OUT - Passive PoE ("+"-": 4, 5 pins; "-": 7, 8 pins)</li> <li>• Power</li> <li>• DATA - 2-wire</li> </ul>	...
Transmission speed	...	...	10 Mbps	...
Main features	...	...	...	<ul style="list-style-type: none"> <li>• D-WDR - Wide Dynamic Range</li> <li>• 2D-DNR - Digital Noise Reduction</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• AGC - Automatic Gain Control</li> <li>• ICR - Movable InfraRed filter</li> <li>• Mirror - Mirror image</li> <li>• Auto White Balance</li> <li>• Sharpness - sharper image outlines</li> </ul>
OSD menu	...	...	...	OSD menu available via DAHUA recorder
Transmission range	...	...	<ul style="list-style-type: none"> <li>• 1000 m @ 2-wire</li> <li>• 100 m @ UTP : Switch PoE - ETH10-2WIRE-TX</li> <li>• 100 m @ UTP : ETH10-2WIRE-RX - IP Camera</li> </ul>	...
Color	...	...	...	White
Vandal-proof	...	...	...	—
LED indicators	...	...	<ul style="list-style-type: none"> <li>• Power</li> <li>• LAN</li> <li>• 2-wire</li> </ul>	...
Operation temp	...	...	...	-40 °C ... 60 °C
Protections	...	...	<ul style="list-style-type: none"> <li>• Overvoltage - LAN, DATA</li> <li>• Protection against reverse polarity connection - Power</li> <li>• Overload 0.6 A - PoE IN ETH10-2WIRE-TX</li> </ul>	...



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Supported languages	...	...	...	Polish, English, French, Spanish, German, Portuguese, Russian, Italian
Main features	<ul style="list-style-type: none"> <li>• Range : ~ 15 cm</li> <li>• The TK-4100 chip</li> </ul>	...	<ul style="list-style-type: none"> <li>• Plug &amp; Play</li> <li>• Support for IP cameras and network devices</li> <li>• Full transparency for networks</li> <li>• Operation modes - Set with jumpers</li> </ul>	...
Power supply	...	...	ETH10-2WIRE-TX : <ul style="list-style-type: none"> <li>• 30 ... 56 V DC - PoE</li> <li>• 10 ... 56 V DC - Power</li> </ul> ETH10-2WIRE-RX : <ul style="list-style-type: none"> <li>• 10 ... 56 V - Power</li> <li>• The output PoE voltage is equal to the input voltage</li> </ul>	12 V DC / 220 mA
Power consumption	...	...	1.35 W (total)	≤ 2.7 W
Housing	...	...	Plastic (PC)	Dome, Aluminum
"Index of Protection"	...	...	IP20	IP67
Operation temp	...	-10 °C ... 50 °C	-25 °C ... 65 °C	...
Weight	0.006 kg	0.08 kg	0.03 kg (single element)	0.27 kg
Dimensions	85 x 54 x 2 mm	110 x 53 x 37 mm	51 x 51 x 24 mm (single element)	Ø 94 x 78 mm
Manufacturer / Brand	ATLO	ATLO	ATTE	DAHUA
Guarantee	2 years	2 years	3 years	3 years