






	AHD, HD-CVI, HD-TVI, PAL CAMERA BCS-B-TA15FSR4(2.0) - 5 Mpx 2.8 mm BCS BASIC	POE SWITCH / EXTENDER PFT1310 3-PORT	SWITCH POE SPS-4P/1 5-PORT	SWITCH POE APTI-POE0802G-120W 8-PORT	MOUNTING RAIL DIN TS-35 OMI-5-DIN/IT FOR OMI-5/IT ENCLOSURE SATEL
					
	363.84 NOK 363.84 NOK	223.45 NOK 223.45 NOK	577.67 NOK 577.67 NOK	756.79 NOK 756.79 NOK	302.41 NOK 302.41 NOK
Length	281 mm
Material	Steel galvanized
Standard	AHD, HD-CVI, HD-TVI, PAL
LAN ports	...	<ul style="list-style-type: none"> • 1 x RJ45 10/100 Base-T + power input : PoE (802.3af/at), • 2 x RJ45 10/100 Base-T + PoE (802.3af) 	5 x RJ45 (4 x PoE (802.3af))	10 x RJ45 (8 x PoE (802.3af/at))	...
Management	...	—	—	—	...
LED diodes	...	LAN, PoE	Power, PoE, Gigabit Ethernet, Link/Act	LAN, PoE	...
Transmission speed	...	10 / 100 Mbps	10 / 100 Mbps : 1 Port LAN + 4 LAN & PoE ports	<ul style="list-style-type: none"> • 10 / 100 / 1000 Mbps : 2 x Port LAN, • 10 / 100 Mbps : 8 x LAN & PoE ports 	...
Maximal total power	65 W	120 W	...
Maximal output power	...	<ul style="list-style-type: none"> • 15.4 W @ port PoE - First device • 3 W @ port PoE - Second device in cascade 	15.4 W / port PoE	30 W / port PoE	...
MAC addresses table	1k	2k	...
Resolution	2880 x 1620 - 5 Mpx - HD-CVI only : Aspect Ratio 16 : 9 , 2592 x 1944 - 5 Mpx - AHD / HD-TVI only , 2560 x 1440 - 4 Mpx , 1920 x 1080 - 1080p , 960 x 576 - 960H
Sensor	1/2.7 " Progressive Scan CMOS
Main features	...	<ul style="list-style-type: none"> • Possibility to connecting in cascade • The device can function as a LAN network and PoE power extender 	...	<ul style="list-style-type: none"> • 2 x Port Uplink • Range PoE : 200 m - The EXTEND mode enabled 	<ul style="list-style-type: none"> • Dedicated for mounting in the OMI-5 enclosure, • Mounting brackets included in the set
Lens	2.8 mm, F1.2
Certificates	CE	CE	...
View angle	109 °
Range of IR illumination	40 m
IR illuminator power adjustment	Automatic
Operation temp	-20 °C ... 70 °C	0 °C ... 55 °C	...
Range	...	100 m - Input 100 m - Output
Protections	...	Overvoltage
Video output	AHD / HD-CVI / HD-TVI / PAL, 1 Vpp / 75 Ω
OSD menu	✓
Operation temp. / Relative humidity	...	-30 ... 65 °C / 10 ... 90 %

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Main features	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • DNR - Digital Noise Reduction • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • Sharpness - sharper image outlines • AGC - Automatic Gain Control • White Balance - ATW/Manual • Day/night mode • ICR - Movable InfraRed filter • Mirror - Mirror image
Power supply	12 V DC / 290 mA	PoE (802.3af/at)	52 V DC / 1.25 A (power adapter included)	230 V AC	...
Power consumption	≤ 3.4 W	0.3 W
Housing	Compact, Metal	Plastic, DIN, TS-35 rail mounting
Color	White
"Index of Protection"	IP67
Operation temp	-30 °C ... 60 °C
Weight	0.241 kg	0.05 kg	0.2 kg	0.74 kg	0.17 kg
Dimensions	Ø 66 x 154 mm	79 x 52 x 23 mm	113 x 93 x 24 mm	220 x 143 x 41 mm	281 x 35 x 43 mm
Manufacturer / Brand	BCS BASIC	APTI	SATEL
Guarantee	2 years	2 years	2 years	2 years	2 years