


	<a href="#">IP CAMERA DS-2CD2T46G2-2I(2.8mm) - 5 Mpx Hikvision</a>	<a href="#">KRONE PROFILE DISCONNECTION MODULE LSA-ZL/10</a>
		
	1885.05 DKK 1885.05 DKK	15.34 DKK 15.34 DKK
Standard	TCP/IP	...
Sensor	1/2.7 " Progressive Scan CMOS	...
Scanning system	Progressive	...
Matrix size	5 Mpx	...
Resolution	2592 x 1944 - 5 Mpx , 2688 x 1520 - 4 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p	...
Lens	2.8 mm	...
View angle	• 103 ° (manufacturer data) • 95 ° (our tests result)	...
Compression	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...
Range of IR illumination	60 m	...
Alarm inputs / outputs	—	...
Audio	—	...
Memory card slot	Micro SD memory cards up to 256GB support (possible local recording)	...
Main stream frame rate	20 fps @ 5 Mpx 25 fps @ 4 Mpx	...
Network interface	10/100 Base-T (RJ-45)	...
Network protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, SFTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, IEEE 802.1x, QoS, IPv6, UDP, Bonjour, SSL / TLS	...
WEB Server	Built-in	...
Max. number of on-line users	6	...
ONVIF	✓	...
Mobile phones support	Port no.: 8000 or access by a cloud (P2P) • Android: Free application <a href="#">iVMS-4500</a> or <a href="#">Hik-Connect</a> • iOS (iPhone): Free application <a href="#">iVMS-4500</a> or <a href="#">Hik-Connect</a>	...
Default admin user / password	admin / - The administrator password should be set at the first start	...
Default IP address	192.168.1.64	...
Web browser access ports	80	...

PC client access ports	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application	...
Mobile client access ports	8000	...
Port ONVIF	80	...
RTSP URL	<ul style="list-style-type: none"> <li>• Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ - with authorization</li> <li>• Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/ - with authorization</li> </ul>	...
RS-485 interface	—	...
Main features	<ul style="list-style-type: none"> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners</li> <li>• ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its</li> <li>• Possibility to change the resolution, quality and bit rate</li> <li>• Configurable Privacy Zones</li> <li>• Motion Detection</li> <li>• Sharpness - sharper image outlines</li> <li>• Camera from AcuSense series</li> <li>• Filtering of false alarms based on the recognition of persons and vehicles</li> <li>• Intelligent image analysis : intrusion, crossing the line (tripwire), detection of entry into the area / exit from the area, scene changing, face detection, advanced face capture features</li> </ul>	...
Power supply	<ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 880 mA</li> </ul>	...
Power consumption	<ul style="list-style-type: none"> <li>≤ 9 W @ PoE (802.3af)</li> <li>≤ 7.5 W @ 12 V DC</li> </ul>	...
Housing	Compact, Aluminum	...
Color	White	...
"Index of Protection"	IP67	...
Operation temp	-30 °C ... 60 °C	...
Supported languages	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Italian	...
Weight	1.07 kg	...
Dimensions	Ø 105 x 290 mm	...
Manufacturer / Brand	Hikvision	...
SAP Code	311311201	...
Guarantee	3 years	...