







	<a href="#">COAXIAL CABLE RF-7 50 Ω</a>	<a href="#">LITHIUM BATTERY BAT- CR2032*P4 ENERGIZER</a>	<a href="#">ALKALINE BATTERY BAT- LR41/GP GP</a>	<a href="#">DISK ARRAY ESS1504C 24 TB DAHUA</a>	<a href="#">WIRELESS DOORBELL BUTTON ATLO-AD-ML30</a>	<a href="#">HDD ENCLOSURE Y-3035 UNITEK</a>
						
	3.17 AUD 3.17 AUD	4.65 AUD 4.65 AUD	0.25 AUD 0.25 AUD	1150.63 AUD 1150.63 AUD	7.18 AUD 7.18 AUD	51.39 AUD 51.39 AUD
Support	...	...	...	...	alarm control panel ATLO-AZ-WG13A-TUYA	...
Battery power supply	...	...	...	...	1 x CR2032 3V	...
Frequency range	...	...	...	...	433 MHz	...
Transmission range	...	...	...	...	≤ 100 m (in open area)	...
In package	...	<b>4 pcs The price for package</b>	...	...	...	...
In section	<b>100 m . Price for 1m when buying a whole roll</b>	...	...	...	...	...
Rated voltage	...	3 V	1.5 V	...	...	...
Supported hard drives	...	...	...	4 x SATA - max. 24 TB (total)	...	1 x SATA III, 2.5 " / 3.5 "
Inner conductor	Ø 1.85 mm Cu ± 0.05 mm - Cu stranded wire	...	...	...	...	...
Operation state indication	...	...	...	...	...	LED diodes
Dielectric	Ø 5 mm - Physical foam	...	...	...	...	...
"Index of Protection"	...	...	...	...	...	...
Outputs	...	...	...	• 1 x eSATA - 3 Gb/s (DVR) • 1 x USB 3.0 B (computer)	...	1 x USB 3.1, max. 5 Gb/s
Shield	Double-sided foil - Cu/PET/Cu	...	...	...	...	...
Write transfer rate	...	...	...	64 MB/s	...	...
Braid	80 % Cu	...	...	...	...	...
Housing	...	...	...	...	...	Desktop, Plastic
Read speed	...	...	...	64 MB/s	...	...
Impedance	50 Ω	...	...	...	...	...
Power supply	...	...	...	100 V ... 240 V AC	...	12 V DC / 2 A (power adapter included)
Outer coating	Ø 7.3 mm ± 0.2 mm PE - Black	...	...	...	...	...
Power consumption	...	...	...	6.8 W (without HDD)	...	...
Type (size)	...	CR2032	LR41 / SR41 / SG3 / G3 / G3A / GP192 / 192 / 392 / V3GA / S312E / MS312 / S736 / RW87 / L736 / LR736	...	...	...
Operation temp	...	...	...	0 °C ... 40 °C	-10 °C ... 50 °C	...
Permissible relative humidity	...	...	...	10 % ... 90 %	≤ 85 %	...
Weight	...	0.002 kg	0.001 kg	4.29 kg	0.02 kg	0.2 kg
Main features	<ul style="list-style-type: none"> <li>• low attenuation</li> <li>• perfect matched</li> <li>• high screening efficiency</li> <li>• it can be used in WLAN 2,4GHz and 5GHz installations</li> <li>• Operation temp : -30 °C ... 70 °C</li> </ul>	...	...	...	<ul style="list-style-type: none"> <li>• Housing - Plastic, Surface-mounted</li> <li>• LED indication</li> <li>• Low power consumption &lt; 10 µA</li> </ul>	...
Dimensions	...	Ø 20 x 3.2 mm	Ø 7.9 x 3.6 mm	440 x 408 x 70 mm - RACK 19", 1.5U	Ø 50 x 13 mm	183 x 117 x 35 mm
Manufacturer / Brand	...	ENERGIZER	GP	DAHUA	ATLO	UNITEK
Cable attenuation at 100m section	2 dB @ 10 MHz 6.4 dB @ 100 MHz 9.1 dB @ 200 MHz 14.1 dB @ 500 MHz 20.9 dB @ 800 MHz 25.9 dB @ 1 GHz 31 dB @ 1.5 GHz 35 dB @ 2 GHz 39 dB @ 2.5 GHz	...	...	...	...	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Maximum transmitted power	3.27 kW @ 10 MHz 1.025 kW @ 100 MHz 0.693 kW @ 200 MHz 0.452 kW @ 500 MHz 0.310 kW @ 800 MHz 0.253 kW @ 1 GHz 0.219 kW @ 1.5 GHz 0.195 kW @ 2 GHz 0.175 kW @ 2.5 GHz	...	...	...	...	...
Guarantee	2 years	2 years	2 years	3 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00