




	COAXIAL CABLE TRI-LAN-240 50 Ω	AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-HDW1231TLMQ-A-0280B - 1080p 2.8 mm DAHUA
		
	0.95 EUR 0.95 EUR	83.45 EUR 83.45 EUR
In section	100 m . Price for 1m when buying a whole roll	...
Standard	...	HD-CVI, HD-TVI, AHD, CVBS
Sensor	...	1/2.8 " Progressive Scan CMOS
Matrix size	...	2.1 Mpx
Inner conductor	Ø 1.4 mm Cu ± 0.02 mm Wire	...
Dielectric	Ø 3.8 mm Physical foam	...
Shield	Foil - Al/PET/Al	...
Resolution	...	1920 x 1080 - 1080p , 960 x 576 - 960H, PAL
Range of IR illumination	...	30 m
IR illuminator power adjustment	...	Automatic
Braid	112 x Ø 0.12 mm Stranded wire CuSn	...
Lens	...	2.8 mm
Impedance	50 Ω	...
Outer coating	Ø 6.1 mm ± 0.02 mm PE	...
View angle	...	• 107 ° (manufacturer data) • 100 ° (our tests result)
S/N ratio	...	> 65 dB
Video output	...	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω
Main features	<ul style="list-style-type: none"> • low attenuation • perfect matched • high screening efficiency • it can be used in WLAN 2,4GHz and 5GHz installations • Operation temp : -40 °C ... 70 °C • Minimal bend radius : 30 / 60 mm 	...
Audio	...	<ul style="list-style-type: none"> • Microphone built-in, • Audio support via coaxial cable - HD-CVI only

Main features	...	<ul style="list-style-type: none"> • WDR - 130 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • BLC/HLC - Back Light / High Light Compensation • ICR - Movable InfraRed filter • Auto White Balance • Day/night mode • AGC - Automatic Gain Control • Privacy zones - max. 8 • Mirror - Mirror image • Sharpness - sharper image outlines
OSD menu	...	OSD menu available via DAHUA recorder
Power supply	...	12 V DC / 260 mA
Power consumption	...	≤ 3.1 W
Housing	...	Dome, Metal + Plastic
"Index of Protection"	...	IP67
Color	...	White
Vandal-proof	...	—
Operation temp	...	-40 °C ... 60 °C
Weight	...	0.33 kg
Cable attenuation at 100m section	Temperature : 20 °C 4.2 dB @ 30 MHz 5.4 dB @ 50 MHz 9.2 dB @ 150 MHz 11.2 dB @ 220 MHz 16.2 dB @ 450 MHz 23.3 dB @ 900 MHz 30.7 dB @ 1500 MHz 33.9 dB @ 1800 MHz 35.9 dB @ 2000 MHz 40.6 dB @ 2500 MHz 65.2 dB @ 5800 MHz	...
Dimensions	...	Ø 110 x 88 mm
Manufacturer / Brand	...	DAHUA
Maximum transmitted power	1.41 kW @ 30 MHz 1.09 kW @ 50 MHz 0.62 kW @ 150 MHz 0.51 kW @ 220 MHz 0.35 kW @ 450 MHz 0.24 kW @ 900 MHz 0.19 kW @ 1500 MHz 0.17 kW @ 1800 MHz 0.16 kW @ 2000 MHz 0.14 kW @ 2500 MHz 0.09 kW @ 5800 MHz	...

Guarantee	2 years	3 years
-----------	---------	---------



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00