




	<a href="#">POWER DISTRIBUTION UNIT PR-1.5M-3G/B (3 OUTLETS) 1.3 m</a>	<a href="#">CRIMPING TOOL HT-303</a>	<a href="#">VIDEO DOORPHONE S1202A VIDOS</a>
			
	3.58 EUR 3.58 EUR	17.60 EUR 17.60 EUR	168.09 EUR 168.09 EUR
Compatibility	...	...	VIDOS DUO
Material	...	Metal / PET	...
Rated voltage	220 ... 240 V AC / 50 Hz	...	...
Sensor	...	...	1/2.7 " Fish Eye CMOS, 2 Mpx
Total maximal current	10 A	...	...
View angle	...	...	170 °
Maximal total load	2500 W	...	...
Application	...	Crimping terminals : 0.5 - 1 mm <sup>2</sup> , 1.5 - 2.5 mm <sup>2</sup> , 4 - 6 mm <sup>2</sup>	...
IR illuminator	...	...	—
Number of outlets	3 grounded outlets 10A/250V CEE 7/5	...	...
LED illuminator	...	...	✓
Fuse	—	...	...
Switch	—	...	...
proximity reader built-in	...	...	Standard : Unique EM 125kHz
Wire gauge	3 x 1.5 mm <sup>2</sup>	...	...
The number of subscribers served	...	...	2
Length of the cable	1.3 m	...	...
Video output	...	...	compatible with the VIDOS DUO digital video doorphone system

Main features	...	High durability tool, made from high quality materials	<ul style="list-style-type: none"> <li>• Wiring - 2 wires without polarity</li> <li>• Relay output : 1 pcs or 2 pcs - B5 Module</li> <li>• Support up to 13 indoor devices (monitors / uniphones)</li> <li>• PIR detectors support</li> <li>• Permanent or cyclical zoom-up of the observed image</li> <li>• Electric strikes and electromagnetic locks support</li> <li>• Electric lock supply: 12V DC / max. 300mA</li> <li>• Easy to add and delete users via MASTER key fobs</li> </ul>
Power supply	...	...	24 V DC
Power consumption	...	...	≤ 3 W (operation) ≤ 0.8 W (Standby mode)
Housing	Plastic	...	Acid-proof steel / Plastic, Waterproof
Color	Black	...	Silver
"Index of Protection"	...	...	IP54
Operation temp	...	...	-20 °C ... 55 °C
Weight	0.25 kg	0.35 kg	0.79 kg
Dimensions	154 x 54 x 39 mm	227 x 59 x 18 mm	220 x 119 x 52 mm
Manufacturer / Brand	...	...	VIDOS
Guarantee	2 years	2 years	3 years