



	IP VANDALPROOF CAMERA DH-IPC-HDBW1230EP-02 - 1080p 2.8 mm DAHUA	INSULATION STRIPPER HT-700D
		
	109.07 EUR 109.07 EUR	6.61 EUR 6.61 EUR
Standard	TCP/IP	...
Material	...	Metal / PET
Sensor	1/2.9 " Progressive Scan CMOS	...
Matrix size	2.1 Mpx	...
Scanning system	Progressive	...
Application	...	Wire : 0.2 ... 6 mm ²
Main features	...	<ul style="list-style-type: none"> • Self-adjusting mechanism according to wire size provides excellent wire stripping without damaging the conductor • Possibility to use for flat telephone cables of 8 mm width • Adjustable stop with lengths scale • Cutter • High durability tool, made from high quality materials
Resolution	1920 x 1080 - 1080p 1280 x 1024 - 1.4 Mpx 1280 x 960 - 1.3 Mpx 1280 x 720 - 720p	...
Lens	2.8 mm	...
View angle	<ul style="list-style-type: none"> • 110 ° (manufacturer data) • 100 ° (our tests result) 	...
Range of IR illumination	30 m	...
S/N ratio	> 50 dB	...
RS-485 interface	—	...
Memory card slot	—	...
Image compression method	H.265 / H.264 / MJPEG	...
Alarm inputs / outputs	—	...
Audio	—	...
Bitrate	24 ... 9472 kbps - H.264 14 ... 5632 kbps - H.265	...
Main stream frame rate	25 fps @ 1920 x 1080	...
Network interface	10/100 Base-T (RJ-45)	...
Network protocols	HTTP, HTTPS, IPv4/IPv6, TCP, ARP, RTSP, RTP, UDP, SMTP, FTP, DHCP, DNS, DDNS, PPPoE, QoS, UPnP, NTP, Bonjour, IEEE 802.1x, Multicast, ICMP, IGMP, SNMP	...
WEB Server	Built-in	...

Max. number of on-line users	20	...
ONVIF	16.12	...
Main features	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ICR - Movable InfraRed filter • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • AGC - Automatic Gain Control • Auto White Balance 	...
Power supply	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 310 mA 	...
Power consumption	< 3.7 W	...
Mobile phones support	Port no.: 37777 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application DMSS, Android: Free application IMOU • iOS (iPhone): Free application DMSS, iOS (iPhone): Free application IMOU 	...
Default IP address	192.168.1.108	...
Default admin user / password	admin / admin	...
Web browser access ports	80, 37777	...
PC client access ports	37777	...
Mobile client access ports	37777	...
Port ONVIF	80	...
RTSP URL	rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream	...
Housing	Dome - Metal / Plastic	...
Color	White	...
"Index of Protection"	IP67	...
Vandal-proof	IK10	...
Operation temp	-30 °C ... 60 °C	...
Weight	0.34 kg	0.21 kg
Dimensions	Ø 110 x 81 mm	170 x 88 x 21 mm
Supported languages	English, Polish	...
Manufacturer / Brand	DAHUA	...
Guarantee	3 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00